

## HYDRAULIC PUMPS

### PO 7000

Foot operated double speed pump, developing a maximum pressure of 700 bar.

The pump is supplied with 3 m long high pressure flexible hose complete with female self-lock quick coupler.

Pressure can be withdrawn at any time during operation by depressing the release lever.

A solid shaped stand gives the pump stability during operation.



**New**

Operating pressure bar	Dimensions mm			Weight kg
	length	width	height	
700	680	200	163	9,8

Storage type	Dimensions mm	Weight kg
VAL P21*	820x430xh290	6,74

\*Supplied with the pump



Operating pressure bar	Dimensions mm			Weight kg
	length	width	height	
700	372	223	482	21

The pump is supplied with:

- high pressure flexible hose with male and female automatic quick coupler
- remote hand controller
- external supply connection cable

Available as optional accessories:

- RCP-B70 remote foot controller
- CS-CPE-1 transportation trolley



Operating pressure bar	Dimensions mm			Weight kg
	length	width	height	
700	343	162	353	19,5*

\*without accessories

- Remote control cable
- External 12V dc supply cable
- Back-up 12V dc battery
- Battery charger 240 V ac supply cable
- Canvas holdall for carrying accessories

Available as optional accessories:

- Remote pedal control
- External battery charger

The control pedal allows for advancing and pressure release at any stage of the operation.

The unit is provided with a 3 m high pressure flexible hose, including a 3/8" NPT female self-lock quick coupler.



Operating pressure bar	Dimensions mm			Weight kg
	length	width	height	
700	220	220	350	12

The control pedal allows for advancing and pressure release at any stage of the operation.

The unit is provided with a 2 m high pressure flexible hose, including a 3/8" NPT female self-lock quick coupler.



Operating pressure bar	Dimensions mm			Weight kg
	length	width	height	
700	320	150	200	6,8

### CPE-1 CPE-1-110

Electrically driven hydraulic pump, powered by a 230V / 50-60Hz single-phase electric motor.

The remote hand controller allows advancement and pressure release on completion of the crimping operation.

The mechanically actuated emergency button located on the pump body allows the pressure release at any time in case of power shortage.

Also available CPE-1-110 version for 110-115V / 50-60Hz.

Both models are IP 55 rated.



### CPE-0-P12N

Portable electro-hydraulic pump, operating at 12 V, and developing a pressure of 700 bar.

This pump can either be operated by battery for independent use, or by an external 12V dc supply.

Complete with internal battery charger;

CPE-0-P12N is supplied with:

- 3 m flexible hose complete with male + female 3/8" NPT self-lock quick couplers



### CPP-1

The CPP-1 air hydraulic power unit intensifies an air supply of 3÷6 bar (60-120 psi) to a power crimping or cutting force of up to 700 bar (10.000 psi) depending upon the input pressure.



### CPP-0

The CPP-0 air hydraulic power unit intensifies an air supply of 6÷8 bar (87-115 psi) to a power crimping or cutting force of up to 700 bar (10.000 psi) depending upon the input pressure.

