

HYDRAULIC PUMPS

PO 7000

New foot operated double speed pump, developing a maximum pressure of 10,000 psi.

The pump is supplied with 10FT long high pressure flexible hose complete with female self-lock quick coupler.

Pressure can be withdrawn at any time during operation by depressing the release lever.

A solid shaped stand gives the pump stability during operation.



Operating pressure psi	Dimensions in.			Weight lbs
	length	width	height	
10,000	26.8	7.9	6.4	21.6

Storage type	Dimensions in.	Weight lbs.
VAL P21*	32.3x16.9x11.4	14.8

*Supplied with the pump



CPE-1-110

Electrically driven hydraulic pump, powered by a 110-115V / 50-60Hz single-phase electrical motor.

The remote hand controller allows advancement and pressure release on completion of the crimping operation.

The mechanically actuated emergency button located on the pump body, allows the pressure release at any time also in case of power shortage.

This model is IP 55 rated.

It is equipped with:

- high pressure flexible hose with female automatic quick coupler
- remote hand controller
- external supply connection cable



Technical details:

- Oil in the reservoir: 0.52 gallons
- Power of motor: 1,050 W
- Delivery of oil: 0.21 Gpm at no load



Operating pressure psi	Dimensions in.			Weight lbs.
	length	width	height	
10,000	14.6	8.8	18.8	46.2

Available as optional accessories:

- RCP-B70 remote foot controller
- CS-CPE-1 transportation trolley



RCP-B70

CS-CPE-1

CPP-1

The CPP-1 air hydraulic power unit intensifies an air supply of 60-120 psi (3÷6 bar) to a power crimping or cutting force of up to 10,000 psi (700 bar) depending upon the input pressure.

The control pedal allows for advancing and pressure release at any stage of the operation.



The unit is provided with a 10 FT high pressure flexible hose, including a 3/8" NPT female self-lock quick coupler.



Operating pressure psi	Dimensions in.			Weight lbs.
	length	width	height	
10,000	8.7	8.7	13.8	26.5

CPP-0

The CPP-0 air hydraulic power unit intensifies an air supply of 87-115 psi (6÷8 bar) to a power crimping or cutting force of up to 10,000 psi (700 bar) depending upon the input pressure.

The control pedal allows for advancing and pressure release at any stage of the operation.



The unit is provided with a 6.5 FT high pressure flexible hose, including a 3/8" NPT female self-lock quick coupler.



Operating pressure psi	Dimensions in.			Weight lbs.
	length	width	height	
10,000	12.6	5.9	7.9	15