

PUSH BUTTON LEGENDS MG-PTS

precut

Push-out the Ø 22.5 or 31 mm blank to locate and secure the legend behind the manual operator head. Consult us for availability of other colours.



CERTIFICATES 

 2011/65/EU

LABORATORY TEST 

CEI EN 60950-1

INDELIBILITY

Information technology equipment - Safety

Part 1: General requirements

§ 1.7.11 Durability

Compliance is checked by inspection and by rubbing the marking by hand for 15 s with a piece of cloth soaked with water and again for 15 s with a piece of cloth soaked with hexane.

After this test, the marking shall be legible; it shall not be possible to remove marking plates easily and they shall show no curling.

CEI EN 61010-1

INDELIBILITY

Ed.2 equivalent to VDE 0411-1

Safety indications for electric devices for measurement, control and laboratory use

Part 1: General indications

This regulation requires that both material and the print shall withstand, cleaning with chemical agents commonly used in industry.

By rubbing manually by hand, without excessive pressure, for 30 seconds with a cloth soaked in the specific detergent or, if not specified, Isopropyl Alcohol.

CEMBRE STANDARD

INDELIBILITY

This test was created to simulate cleaning with chemical products commonly used on various surfaces.

By wiping with a cloth soaked in 95% Ethanol 30 times and making a visual inspection after every 10 passes.

DIN 30643

PUSH BUTTON LEGENDS MG-PTS

Technical characteristics

Geometric shape	rectangular with square corners
Precut	yes
Silicon free	yes



PUSH BUTTON LEGENDS MG-PTS

List of products

MG-PTS.							
Material							Rigid PVC
UL94 class							V0
Min operating temperature range							-30 °C
Max operating temperature range							60 °C
Type	Colour	Height	Length	Diameter of the hole	Quantity per sheet	Pack qty	SWcode
MG-PTS 15092	White	39 mm	30 mm	22.5 mm	6	300	1002
MG-PTS 15042	Yellow	39 mm	30 mm	22.5 mm	6	300	1002
MG-PTS 15082GY	Grey	39 mm	30 mm	22.5 mm	6	300	1002
MG-PTS 15022	Red	39 mm	30 mm	22.5 mm	6	300	1002
MG-PTS 15002	Black	39 mm	30 mm	22.5 mm	6	300	1002
MG-PTS 15090	White	40 mm	30 mm	22.5 mm	6	300	1000
MG-PTS 15040	Yellow	40 mm	30 mm	22.5 mm	6	300	1000
MG-PTS 15080GY	Grey	40 mm	30 mm	22.5 mm	6	300	1000
MG-PTS 15020	Red	40 mm	30 mm	22.5 mm	6	300	1000
MG-PTS 15000	Black	40 mm	30 mm	22.5 mm	6	300	1000
MG-PTS 15091	White	50 mm	30 mm	22.5 mm	6	300	1001
MG-PTS 15041	Yellow	50 mm	30 mm	22.5 mm	6	300	1001
MG-PTS 15081GY	Grey	50 mm	30 mm	22.5 mm	6	300	1001
MG-PTS 15001	Black	50 mm	30 mm	22.5 mm	6	300	1001
MG2-PTS 15094	White	60 mm	62 mm	31 mm	4	200	1003
MG2-PTS 15044	Yellow	60 mm	62 mm	31 mm	4	200	1003
MG2-PTS 15084GY	Grey	60 mm	62 mm	31 mm	4	200	1003
MG2-PTS 15024	Red	60 mm	62 mm	31 mm	4	200	1003
MG2-PTS 15064	Blue	60 mm	62 mm	31 mm	4	200	1003
MG2-PTS 15004	Black	60 mm	62 mm	31 mm	4	200	1003

MG-PTS-HF

Material	Polycarbonate
UL94 class	V0
Halogen Free	yes
Max operating temperature range	-40 °C
Min operating temperature range	130 °C

Type	Colour	Height	Length	Diameter of the hole	Quantity per sheet	Pack qty	SWcode
MG-PTS 15082-HF	Metallic grey	39 mm	30 mm	22.5 mm	6	300	1002
MG-PTS 15080-HF	Metallic grey	40 mm	30 mm	22.5 mm	6	300	1000
MG-PTS 15081-HF	Metallic grey	50 mm	30 mm	22.5 mm	6	300	1001
MG2-PTS 15084-HF	Metallic grey	60 mm	62 mm	31 mm	4	200	1003