

PUSH BUTTON LEGENDS MG-PTSA

precut

Push-out the Ø 22.5 or 31 mm blank to locate and secure the legend behind the manual operator head. Consult us for availability of other colours.



CERTIFICATES 

 2011/65/EU

LABORATORY TEST 

CEI EN 60950-1

INDELIBILITY

Information technology equipment - Safety

Part 1: General requirements

§ 1.7.11 Durability

Compliance is checked by inspection and by rubbing the marking by hand for 15 s with a piece of cloth soaked with water and again for 15 s with a piece of cloth soaked with hexane.

After this test, the marking shall be legible; it shall not be possible to remove marking plates easily and they shall show no curling.

CEI EN 61010-1

INDELIBILITY

Ed.2 equivalent to VDE 0411-1

Safety indications for electric devices for measurement, control and laboratory use

Part 1: General indications

This regulation requires that both material and the print shall withstand, cleaning with chemical agents commonly used in industry.

By rubbing manually by hand, without excessive pressure, for 30 seconds with a cloth soaked in the specific detergent or, if not specified, Isopropyl Alcohol.

CEMBRE STANDARD

INDELIBILITY

This test was created to simulate cleaning with chemical products commonly used on various surfaces.

By wiping with a cloth soaked in 95% Ethanol 30 times and making a visual inspection after every 10 passes.

DIN 30643

PUSH BUTTON LEGENDS MG-PTSA

Technical characteristics

Geometric shape	rectangular with square corners
Precut	yes
UL94 class	V0
Silicon free	yes
Adhesive	yes



PUSH BUTTON LEGENDS MG-PTSA

List of products

MG-PTSA.							
Material							Rigid PVC
Min operating temperature range							-30 °C
Max operating temperature range							60 °C
Type	Colour	Height	Length	Diameter of the hole	Quantity per sheet	Pack qty	SWcode
MG-PTSA 15122	Red	39 mm	30 mm	22.5 mm	6	150	1002
MG-PTSA 15142	Yellow	39 mm	30 mm	22.5 mm	6	150	1002
MG-PTSA 15182GY	Grey	39 mm	30 mm	22.5 mm	6	150	1002
MG-PTSA 15102	Black	39 mm	30 mm	22.5 mm	6	150	1002
MG-PTSA 15100	Black	40 mm	30 mm	22.5 mm	6	150	1000
MG-PTSA 15120	Red	40 mm	30 mm	22.5 mm	6	150	1000
MG-PTSA 15181GY	Grey	50 mm	30 mm	22.5 mm	6	150	1001
MG-PTSA 15180GY	Grey	40 mm	30 mm	22.5 mm	6	150	1000
MG-PTSA 15140	Yellow	40 mm	30 mm	22.5 mm	6	150	1000
MG-PTSA 15191	White	50 mm	30 mm	22.5 mm	6	150	1001
MG-PTSA 15190	White	40 mm	30 mm	22.5 mm	6	150	1000
MG-PTSA 15141	Yellow	50 mm	30 mm	22.5 mm	6	150	1001
MG-PTSA 15101	Black	50 mm	30 mm	22.5 mm	6	150	1001
MG2-PTSA 15164	Blue	60 mm	62 mm	31 mm	4	100	1003
MG2-PTSA 15124	Red	60 mm	62 mm	31 mm	4	100	1003
MG2-PTSA 15184GY	Grey	60 mm	62 mm	31 mm	4	100	1003
MG2-PTSA 15144	Yellow	60 mm	62 mm	31 mm	4	100	1003
MG2-PTSA 15194	White	60 mm	62 mm	31 mm	4	100	1003
MG2-PTSA 15104	Black	60 mm	62 mm	31 mm	4	100	1003
MG-PTSA 15192	White	39 mm	30 mm	22.5 mm	6	150	1002

MG-PTSA-HF

Material	Polycarbonate
Halogen Free	yes
Max operating temperature range	-40 °C
Min operating temperature range	130 °C

Type	Colour	Height	Length	Diameter of the hole	Quantity per sheet	Pack qty	SWcode
MG-PTSA 15181-HF	Metallic grey	50 mm	30 mm	22.5 mm	6	150	1001
MG-PTSA 15180-HF	Metallic grey	40 mm	30 mm	22.5 mm	6	150	1000
MG2-PTSA 15184-HF	Metallic grey	60 mm	62 mm	31 mm	4	100	1003
MG-PTSA 15182-HF	Metallic grey	39 mm	30 mm	22.5 mm	6	150	1002