

# LEGENDS MG-TAR

*precut*

MG-TAR legends are often designed to fit particular components with a suitable clip-in or stickon location. Consult us for availability of other colours.



CERTIFICATES 

 2011/65/EU

LABORATORY TEST 

## **CEI EN 60950-1**

### **INDELIBILITY**

#### **Information technology equipment - Safety**

*Part 1: General requirements*

*§ 1.7.11 Durability*

Compliance is checked by inspection and by rubbing the marking by hand for 15 s with a piece of cloth soaked with water and again for 15 s with a piece of cloth soaked with hexane.

After this test, the marking shall be legible; it shall not be possible to remove marking plates easily and they shall show no curling.

## **CEI EN 61010-1**

### **INDELIBILITY**

#### **Ed.2 equivalent to VDE 0411-1**

#### **Safety indications for electric devices for measurement, control and laboratory use**

*Part 1: General indications*

This regulation requires that both material and the print shall withstand, cleaning with chemical agents commonly used in industry.

By rubbing manually by hand, without excessive pressure, for 30 seconds with a cloth soaked in the specific detergent or, if not specified, Isopropyl Alcohol.

---

## **CEMBRE STANDARD**

### **INDELIBILITY**

This test was created to simulate cleaning with chemical products commonly used on various surfaces.

By wiping with a cloth soaked in 95% Ethanol 30 times and making a visual inspection after every 10 passes.

---

## **DIN 30643**

---

## LEGENDS MG-TAR

### *Technical characteristics*

Min operating temperature range	-30 °C
Max operating temperature range	80 °C
UL94 class	V0
Material	Rigid PVC
Precut	yes
Geometric shape	rectangular with square corners



## LEGENDS MG-TAR

### List of products

<b>MG-TAR</b>						
Type	Height	Length	Quantity per sheet	Pack qty	SWcode	Colour
MG-TAR 45390	14 mm	45.5 mm	14	700	718	White
MG-TAR 45398	4.6 mm	17.5 mm	25	875	797	White
MG-TAR 45090	6 mm	60 mm	16	800	169	White
MG-TAR 45396	6.3 mm	30 mm	45	2	800	White
MG-TAR 45394	6.3 mm	44 mm	30	750	798	White
MG-TAR 45344	6.3 mm	44 mm	30	750	798	Yellow
MG-TAR 45384GY	6.3 mm	44 mm	30	750	798	Grey
MG-TAR 45324	6.3 mm	44 mm	30	750	798	Red
MG-TAR 45364	6.3 mm	44 mm	30	750	798	Blue
MG-TAR 45098	7.5 mm	40 mm	24	1,200	801	White
MG-TAR 45048	7.5 mm	40 mm	24	1,200	801	Yellow
MG-TAR 45089	8 mm	55 mm	24	1	719	White
MG-TAR 45395	10 mm	28.5 mm	27	1,350	350	White
MG-TAR 45297	10.4 mm	21 mm	50	1,250	351	White
MG-TAR 45392	12 mm	57.5 mm	16	800	708	White
MG-TAR 45192	14 mm	84 mm	6	300	805	White
MG-TAR 45142	14 mm	84 mm	6	300	805	Yellow
MG-TAR 45194	17 mm	35 mm	18	900	711	White
MG-TAR 45144	17 mm	35 mm	18	900	711	Yellow
MG-TAR 45094N	17 mm	40 mm	18	900	713	White
MG-TAR 45044N	17 mm	40 mm	18	900	713	Yellow
MG-TAR 45064N	17 mm	40 mm	18	900	713	Blue
MG-TAR 45195	17 mm	44 mm	12	600	717	White
MG-TAR 45145	17 mm	44 mm	12	600	717	Yellow
MG-TAR 45391	17.5 mm	36 mm	18	900	709	White
MG-TAR 45490	8.5 mm	30 mm	33	1,650	720	White