


DOG TAGS MG-DOG

precut, pre-drilled with one hole

Dog tags are often loosely attached to equipment where a label cannot be fixed, eg on valves, tappings, couplers or in oil/solvent-rich atmospheres. Consult us for availability of other colours.



CERTIFICATES 

 2011/65/EU

LABORATORY TEST 

CEI EN 60950-1

INDELIBILITY

Information technology equipment - Safety

Part 1: General requirements

§ 1.7.11 Durability

Compliance is checked by inspection and by rubbing the marking by hand for 15 s with a piece of cloth soaked with water and again for 15 s with a piece of cloth soaked with hexane.

After this test, the marking shall be legible; it shall not be possible to remove marking plates easily and they shall show no curling.

CEI EN 61010-1

INDELIBILITY

Ed.2 equivalent to VDE 0411-1

Safety indications for electric devices for measurement, control and laboratory use

Part 1: General indications

This regulation requires that both material and the print shall withstand, cleaning with chemical agents commonly used in industry.

By rubbing manually by hand, without excessive pressure, for 30 seconds with a cloth soaked in the specific detergent or, if not specified, Isopropyl Alcohol.

CEMBRE STANDARD

INDELIBILITY

This test was created to simulate cleaning with chemical products commonly used on various surfaces.

By wiping with a cloth soaked in 95% Ethanol 30 times and making a visual inspection after every 10 passes.

DIN 30643

DOG TAGS MG-DOG

Technical characteristics

Silicon free	yes
Precut	yes



DOG TAGS MG-DOG

List of products

MG-DOG.									
Material									Rigid PVC
UL94 class									V0
Max operating temperature range									60 °C
Min operating temperature range									-30 °C
Type	Colour	Height	Length	Diameter	Diameter of the hole	Quantity per sheet	Pack qty	SWcode	Geometric shape
MG-DOG 48380	Green			35 mm	4 mm	6	300	870	circular
MG-DOG 48203	White	20 mm	20 mm		5 mm	25	1,250	867	square with square corners
MG-DOG 48204	White	25 mm	50 mm		5 mm	8	400	868	rectangular with square corners
MG-DOG 48244	Yellow	25 mm	50 mm		5 mm	8	400	868	rectangular with square corners
MG-DOG 48392	White			20 mm	6.5 mm	12	300	875	circular
MG-DOG 48342	Yellow			20 mm	6.5 mm	12	300	875	circular
MG-DOG 48322	Red			20 mm	6.5 mm	12	300	875	circular
MG-DOG 48352	Green			20 mm	6.5 mm	12	300	875	circular
MG-DOG 48391	White			20 mm	5 mm	12	300	874	circular
MG-DOG 48341	Yellow			20 mm	5 mm	12	300	874	circular
MG-DOG 48300	White			35 mm	4 mm	6	300	870	circular
MG-DOG 48340	Yellow			35 mm	4 mm	6	300	870	circular
MG-DOG 48320	Red			35 mm	4 mm	6	300	870	circular

MG-DOG-HF

Material	Polycarbonate
UL94 class	V0
Halogen Free	yes
Min operating temperature range	-40 °C
Max operating temperature range	130 °C

Type	Geometric shape	Colour	Height	Length	Diameter	Diameter of the hole	Quantity per sheet	Pack qty	SWcode
MG-DOG 48204-HF	rectangular with square corners	White	25 mm	50 mm		5 mm	8	400	568
MG-DOG 48397-HF	rectangular with square corners	White	52 mm	107 mm		6.5 mm	2	100	204
MG-DOG 48352-HF	circular	Green			20 mm	6.5 mm	12	300	875
MG-DOG 40205-HF	rectangular with rounded corners	White	19 mm		38 mm	8 mm	8	400	869
MG-DOG 40206-HF	rectangular with rounded corners	White	21 mm		39 mm	12.7 mm	8	400	873
MG-DOG 48300-HF	circular	White			35 mm	4 mm	6	300	870
MG-DOG 48340-HF	rectangular with rounded corners	Yellow			35 mm	4 mm	6	300	870