

LABELS MG2-VYT

self adhesive, precut

Dielectric PVC film labels used for internal and external marking.



CERTIFICATES 

 2011/65/EU

LABORATORY TEST 

CEI EN 60950-1

INDELIBILITY

Information technology equipment - Safety

Part 1: General requirements

§ 1.7.11 Durability

Compliance is checked by inspection and by rubbing the marking by hand for 15 s with a piece of cloth soaked with water and again for 15 s with a piece of cloth soaked with hexane.

After this test, the marking shall be legible; it shall not be possible to remove marking plates easily and they shall show no curling.

CEI EN 61010-1

INDELIBILITY

Ed.2 equivalent to VDE 0411-1

Safety indications for electric devices for measurement, control and laboratory use

Part 1: General indications

This regulation requires that both material and the print shall withstand, cleaning with chemical agents commonly used in industry.

By rubbing manually by hand, without excessive pressure, for 30 seconds with a cloth soaked in the specific detergent or, if not specified, Isopropyl Alcohol.

CEMBRE STANDARD

INDELIBILITY

This test was created to simulate cleaning with chemical products commonly used on various surfaces.

By wiping with a cloth soaked in 95% Ethanol 30 times and making a visual inspection after every 10 passes.

DIN 30643

LABELS MG2-VYT

Technical characteristics

Material	PVC film
Geometric shape	rectangular with square corners
Min operating temperature range	-40 °C
Max operating temperature range	80 °C
Min application temperature	10 °C
Max application temperature	40 °C
Precut	yes
Adhesive	yes



LABELS MG2-VYT

List of products

MG2-VYT						
Type	Colour	Height	Length	Quantity per sheet	Pack qty	SWcode
MG-VYT 46942	White	110 mm	140 mm	1	50	273
MG-VYT 46442	Yellow	110 mm	140 mm	1	50	273
MG-VYT 46842	Metallic grey	110 mm	140 mm	1	50	273