


PANEL PLATES MG-VRT-AH

self adhesive, customisable

MG-VRT-AH rigid PVC panel plates are used to create name plates, rating plates, data plates using company logos, technical data, serial numbers, EC certification, etc. CPT transparent polycarbonate covers can be used for increased durability. Consult us for availability of other colours.
 Note: UV resistance may vary between colours.



CERTIFICATES 

 2011/65/EU

LABORATORY TEST 

CEI EN 60950-1

INDELIBILITY

Information technology equipment - Safety

Part 1: General requirements

§ 1.7.11 Durability

Compliance is checked by inspection and by rubbing the marking by hand for 15 s with a piece of cloth soaked with water and again for 15 s with a piece of cloth soaked with hexane.

After this test, the marking shall be legible; it shall not be possible to remove marking plates easily and they shall show no curling.

CEI EN 61010-1

INDELIBILITY

Ed.2 equivalent to VDE 0411-1

Safety indications for electric devices for measurement, control and laboratory use

Part 1: General indications

This regulation requires that both material and the print shall withstand, cleaning with chemical agents commonly used in industry.

By rubbing manually by hand, without excessive pressure, for 30 seconds with a cloth soaked in the specific detergent or, if not specified, Isopropyl Alcohol.

CEMBRE STANDARD

INDELIBILITY

This test was created to simulate cleaning with chemical products commonly used on various surfaces.

By wiping with a cloth soaked in 95% Ethanol 30 times and making a visual inspection after every 10 passes.

DIN 30643

PANEL PLATES MG-VRT-AH

Technical characteristics

Geometric shape	rectangular with square corners
Silicon free	yes
UL94 class	V0
Material	Rigid PVC
Adhesive	yes
Rivet fixing	yes
Min operating temperature range	-30 °C
Max operating temperature range	60 °C
Min application temperature	10 °C
Max application temperature	40 °C



PANEL PLATES **MG-VRT-AH**

List of products

MG-VRT-AH

Type	Height	Length	Diameter of the hole	No. hole	Quantity per sheet	Pack qty	SWcode	Colour
MG-VRT-AH 88211	50 mm	100 mm		4	2	50	811	Red
MG-VRT-AH 88940	15 mm	52 mm	4 mm	2	14	350	831	White
MG-VRT-AH 88140	15 mm	52 mm	4 mm	2	14	350	831	Black
MG-VRT-AH 88920	20 mm	40 mm	4 mm	2	10	250	864	White
MG-VRT-AH 88420	20 mm	40 mm	4 mm	2	10	250	864	Yellow
MG-VRT-AH 88720GY	20 mm	40 mm	4 mm	2	10	250	864	Grey
MG-VRT-AH 88906	25 mm	50 mm	4 mm	2	8	200	860	White
MG-VRT-AH 88406	25 mm	50 mm	4 mm	2	8	200	860	Yellow
MG-VRT-AH 88907	25 mm	75 mm	4 mm	2	4	100	809	White
MG-VRT-AH 88407	25 mm	75 mm	4 mm	2	4	100	809	Yellow
MG-VRT-AH 88207	25 mm	75 mm	4 mm	2	4	100	809	Red
MG-VRT-AH 88942	25 mm	80 mm	4 mm	2	4	100	832	White
MG-VRT-AH 88142	25 mm	80 mm	4 mm	2	4	100	832	Black
MG-VRT-AH 88914	25 mm	100 mm	4 mm	2	4	100	206	White
MG-VRT-AH 88414	25 mm	100 mm	4 mm	2	4	100	206	Yellow
MG-VRT-AH 88214	25 mm	100 mm		2	4	100	206	Red
MG-VRT-AH 88941	35 mm	50 mm	4 mm	2	6	150	833	White
MG-VRT-AH 88141	35 mm	50 mm	4 mm	2	6	150	833	Black
MG-VRT-AH 88929	35 mm	75 mm		2	3	75	817	White
MG-VRT-AH 88944	35 mm	85 mm	4 mm	2	3	75	823	White
MG-VRT-AH 88909	35 mm	100 mm	4 mm	2	3	75	818	White
MG-VRT-AH 88910	35 mm	100 mm	4 mm	4	3	75	818	White
MG-VRT-AH 88410	35 mm	100 mm	4 mm	4	3	75	818	Yellow
MG-VRT-AH 88922	42 mm	78 mm	4 mm	2	2	50	819	White
MG-VRT-AH 88422	42 mm	78 mm	4 mm	2	2	50	819	Yellow
MG-VRT-AH 88911	50 mm	100 mm	4 mm	4	2	50	811	White
MG-VRT-AH 88411	50 mm	100 mm	4 mm	4	2	50	811	Yellow
MG-VRT-AH 88915	75 mm	120 mm	4 mm	4	1	25	816	White
MG-VRT-AH 88415	75 mm	120 mm	4 mm	4	1	25	816	Yellow
MG-VRT-AH 88115	75 mm	120 mm	4 mm	4	1	25	816	Black
MG-VRT-AH 88912	105 mm	110 mm	4 mm	4	1	25	859	White
MG-VRT-AH 88412	105 mm	110 mm	4 mm	4	1	25	859	Yellow
MG-VRT-AH 88712GY	105 mm	110 mm	4 mm	4	1	25	859	Grey

