

PANEL PLATES MG2-VRT-AH

self adhesive, customisable


MG2-VRT-AH rigid PVC panel plates offer larger sizes and greater print area.

Consult us for availability of other colours.

Note: UV resistance may vary between colours



CERTIFICATES 

 2011/65/EU

LABORATORY TEST 

CEI EN 60950-1

INDELIBILITY

Information technology equipment - Safety

Part 1: General requirements

§ 1.7.11 Durability

Compliance is checked by inspection and by rubbing the marking by hand for 15 s with a piece of cloth soaked with water and again for 15 s with a piece of cloth soaked with hexane.

After this test, the marking shall be legible; it shall not be possible to remove marking plates easily and they shall show no curling.

CEI EN 61010-1

INDELIBILITY

Ed.2 equivalent to VDE 0411-1

Safety indications for electric devices for measurement, control and laboratory use

Part 1: General indications

This regulation requires that both material and the print shall withstand, cleaning with chemical agents commonly used in industry.

By rubbing manually by hand, without excessive pressure, for 30 seconds with a cloth soaked in the specific detergent or, if not specified, Isopropyl Alcohol.

CEMBRE STANDARD

INDELIBILITY

This test was created to simulate cleaning with chemical products commonly used on various surfaces.

By wiping with a cloth soaked in 95% Ethanol 30 times and making a visual inspection after every 10 passes.

DIN 30643

PANEL PLATES MG2-VRT-AH

Technical characteristics

Geometric shape	rectangular with square corners
Silicon free	yes
UL94 class	V0
Material	Rigid PVC
Adhesive	yes
Rivet fixing	yes
Min operating temperature range	-30 °C
Max operating temperature range	60 °C
Min application temperature	10 °C
Max application temperature	40 °C



PANEL PLATES MG2-VRT-AH

List of products

MG2-VRT-AH								
Type	Height	Length	Diameter of the hole	No. hole	Quantity per sheet	Pack qty	SWcode	Colour
MG2-VRT-AH 88927	25 mm	140 mm	4 mm	2	4	100	871	White
MG2-VRT-AH 88427	25 mm	140 mm	4 mm	2	4	100	871	Yellow
MG2-VRT-AH 88943	29 mm	140 mm	4 mm	2	3	75	834	White
MG2-VRT-AH 88939	35 mm	142 mm	4 mm	2	3	75	835	White
MG2-VRT-AH 88968	40 mm	150 mm	4 mm	2	2	50	781	White
MG2-VRT-AH 88919	50 mm	140 mm	4 mm	4	2	50	872	White
MG2-VRT-AH 88619	50 mm	140 mm	4 mm	4	2	50	872	Blue
MG2-VRT-AH 88956	50 mm	150 mm	4 mm	4	2	50	843	White
MG2-VRT-AH 88938	82 mm	142 mm	4 mm	4	1	25	836	White
MG2-VRT-AH 88237	102 mm	138 mm	4 mm	4	1	25	208	Red
MG2-VRT-AH 88637	102 mm	138 mm	4 mm	4	1	25	208	Blue