

LABELS VCT-ROLL

self adhesive, precut

Dielectric labels on a reel, with permanent adhesive backing and increased resistance to ageing.



CERTIFICATES 



2011/65/EU

LABELS VCT-ROLL

Technical characteristics

Min operating temperature range	-40 °C
Max operating temperature range	140 °C
Min application temperature	10 °C
Max application temperature	40 °C
Material	PVC coated fabric
Precut	yes
Adhesive	yes
Geometric shape	rectangular with square corners



LABELS VCT-ROLL

List of products

VCT-ROLL

Type	Colour	Height	Length	Pack qty	SWcode
VCT-ROLL 48094	White	9 mm	20 mm	17,360	4502
VCT-ROLL 48048	White	6 mm	15 mm	10,000	4100
VCT-ROLL 48043	Yellow	40 mm	7 mm	11,600	4500
VCT-ROLL 48042	Yellow	100 mm	10 mm	3,880	4501
VCT-ROLL 48044	Yellow	9 mm	20 mm	17,360	4502
VCT-ROLL 48142	Yellow	15 mm	50 mm	5,000	4503

Products used together

Printers

Thermal transfer printer for roll media ROLLY3000 - Thermal transfer printer for roll media ROLLY3000

Thermal transfert printer on roll ROLLY2000 990910 - ROLLY2000