

CONTINUOUS MATERIAL TTF

Continuous material is made from materials which are not temperature sensitive and whose surfaces are treated to accept the pigment from the ribbon heated by the print head.



CONTINUOUS MATERIAL TTF



CONTINUOUS MATERIAL TTF

List of products

TTF	
<i>Products used together</i>	
Printers	
Thermal transfer printer for roll media ROLLY3000 - Thermal transfer printer for roll media ROLLY3000	
Thermal transfert printer on roll ROLLY2000 990910 - ROLLY2000 990910	

TTF-WVYG				
Colour				White
Material				PVC film (outdoor)
Thickness				0.08 mm
UV resistance				****
Min operating temperature range				-30 °C
Max operating temperature range				70 °C
Min application temperature				10 °C
Max application temperature				40 °C
Type	Width	Length	Pack qty	SWcode
TTF 8506012WVYG	25.4 mm	125 mm	1	4287
TTF 8506003WVYG	35 mm	125 mm	1	4280
TTF 8506004WVYG	40 mm	125 mm	1	4281
TTF 8506011WVYG	50 mm	125 mm	1	4283
TTF 8506010WVYG	58 mm	125 mm	1	
TTF 8506001WVYG	80 mm	125 mm	1	4282
TTF 8506000WVYG	105 mm	125 mm	1	4284

TTF-YVYG

Material	PVC film (outdoor)
Colour	Yellow
Thickness	0.08 mm
UV resistance	****
Min operating temperature range	-30 °C
Max operating temperature range	70 °C
Min application temperature	10 °C
Max application temperature	40 °C

Type	Width	Length	Pack qty	SWcode
TTF 8506012YVYG	25.4 mm	125 mm	1	4287
TTF 8506000YVYG	105 mm	125 mm	1	4284
TTF 8506001YVYG	80 mm	125 mm	1	4282
TTF 8506003YVYG	35 mm	125 mm	1	4280
TTF 8506004YVYG	40 mm	125 mm	1	4281
TTF 8506011YVYG	50 mm	125 mm	1	4283
TTF 8506010YVYG	58 mm	125 mm	1	

TTF-SVYG

Colour	Metallic grey
Material	PVC film (outdoor)
Thickness	0.07 mm
UV resistance	****
Min operating temperature range	-30 °C
Max operating temperature range	70 °C
Min application temperature	10 °C
Max application temperature	40 °C

Type	Width	Length	Pack qty	SWcode
TTF 8506012SVYG	25.4 mm	125 mm	1	4287
TTF 8506000SVYG	105 mm	125 mm	1	4284
TTF 8506001SVYG	80 mm	125 mm	1	4282
TTF 8506003SVYG	35 mm	125 mm	1	4280
TTF 8506004SVYG	40 mm	125 mm	1	4281
TTF 8506011SVYG	50 mm	125 mm	1	4283
TTF 8506010SVYG	58 mm	125 mm	1	

TTF-PPYG

Material	Polyester film
Colour	Metallic grey
Thickness	0.05 mm
UV resistance	**
Min operating temperature range	-40 °C
Max operating temperature range	140 °C
Min application temperature	10 °C
Max application temperature	40 °C

Type	Width	Length	Pack qty	SWcode
TTF 8506012PPYG	25.4 mm	125 mm	1	4287
TTF 8506000PPYG	105 mm	125 mm	1	4284
TTF 8506001PPYG	80 mm	125 mm	1	4282
TTF 8506003PPYG	35 mm	125 mm	1	4280
TTF 8506004PPYG	40 mm	125 mm	1	4281
TTF 8506011PPYG	50 mm	125 mm	1	4283
TTF 8506010PPYG	58 mm	125 mm	1	

TTF-CPYG

Colour	Transparent
Material	PET
Thickness	0.02 mm
UV resistance	***
Min operating temperature range	-40 °C
Max operating temperature range	125 °C
Min application temperature	10 °C
Max application temperature	40 °C

Type	Width	Length	Pack qty	SWcode
TTF 8506012CPYG	25.4 mm	125 m	1	4287
TTF 8506000CPYG	105 mm	125 m	1	4284
TTF 8506001CPYG	80 mm	125 m	1	4282
TTF 8506003CPYG	35 mm	125 m	1	4280
TTF 8506004CPYG	40 mm	125 m	1	4281
TTF 8506010CPYG	58 mm	125 m	1	4285
TTF 8506011CPYG	50 mm	125 m	1	4283

TTF-WPYG

Colour	White
Material	Polyester film
Thickness	0.05 mm
UV resistance	*
Min operating temperature range	-40 °C
Max operating temperature range	140 °C
Min application temperature	10 °C
Max application temperature	40 °C

Type	Width	Length	Pack qty	SWcode
TTF 8506012WPYG	25.4 mm	125 mm	1	4287
TTF 8506000WPYG	105 mm	125 mm	1	4284
TTF 8506001WPYG	80 mm	125 mm	1	4282
TTF 8506003WPYG	35 mm	125 mm	1	4280
TTF 8506004WPYG	40 mm	125 mm	1	4281
TTF 8506010WPYG	58 mm	125 mm	1	
TTF 8506011WPYG	50 mm	125 mm	1	4283

TTF-WCYG/5

Colour	White
Material	PVC film reflective
Thickness	0.08 mm
UV resistance	****
Min operating temperature range	-30 °C
Max operating temperature range	70 °C
Min application temperature	10 °C
Max application temperature	40 °C

Type	Width	Length	Pack qty	SWcode
TTF 856007WCYG/5	35 mm	24 m	1	4280
TTF 856008WCYG/5	80 mm	24 m	1	4282
TTF 856006WCYG/5	105 mm	24 m	1	4284

TTF-YCYG/5

Colour	Yellow
Material	PVC film reflective
Thickness	0.08 mm
UV resistance	****
Min operating temperature range	-30 °C
Max operating temperature range	70 °C
Max application temperature	40 °C
Min application temperature	10 °C

Type	Width	Pack qty	SWcode	Length
TTF 856007YCYG/5	35 mm	1	4280	24 m
TTF 856008YCYG/5	80 mm	1	4282	24 m
TTF 856006YCYG/5	105 mm	1	4284	24 m

TTF-BCYG/5

Colour	Blue
Material	PVC film reflective
Thickness	0.08 mm
UV resistance	****
Min operating temperature range	-30 °C
Max operating temperature range	70 °C
Min application temperature	10 °C
Max application temperature	40 °C

Type	Width	Pack qty	SWcode
TTF 856009BCYG/5	115 mm	1	4286

TTF-WVRG

Colour	White
Material	Rigid PVC
Thickness	0.4 mm
Min operating temperature range	-30 °C
Max operating temperature range	70 °C

Type	Width	Pack qty	Length
TTF 8506002WVRG	100 mm	1	25 m

TTF-YVRG

Colour	Yellow
Material	Rigid PVC
Thickness	0.4 mm
Min operating temperature range	-30 °C
Max operating temperature range	70 °C

Type	Width	Pack qty	Length
TTF 8506002YVRG	100 mm	1	25 m