

## CONTINUOUS MATERIAL TTF

Continuous material is made from materials which are not temperature sensitive and whose surfaces are treated to accept the pigment from the ribbon heated by the print head.



## CONTINUOUS MATERIAL TTF



# CONTINUOUS MATERIAL TTF

## List of products

**TTF**

*Products used together*

**Printers**

**Thermal transfer printer for roll media ROLLY3000 - Thermal transfer printer for roll media ROLLY3000**

**Thermal transfert printer on roll ROLLY2000 990910 - ROLLY2000**

**TTF-WVYG**

|                                 |                    |
|---------------------------------|--------------------|
| Colour                          | White              |
| Material                        | PVC film (outdoor) |
| Thickness                       | 0.08 mm            |
| UV resistance                   | ****               |
| Min operating temperature range | -30 °C             |
| Max operating temperature range | 70 °C              |
| Min application temperature     | 10 °C              |
| Max application temperature     | 40 °C              |

| Type            | Width   | Length | Pack qty | SWcode |
|-----------------|---------|--------|----------|--------|
| TTF 8506012WVYG | 25.4 mm | 125 mm | 1        | 4287   |
| TTF 8506003WVYG | 35 mm   | 125 mm | 1        | 4280   |
| TTF 8506004WVYG | 40 mm   | 125 mm | 1        | 4281   |
| TTF 8506011WVYG | 50 mm   | 125 mm | 1        | 4283   |
| TTF 8506010WVYG | 58 mm   | 125 mm | 1        |        |
| TTF 8506001WVYG | 80 mm   | 125 mm | 1        | 4282   |
| TTF 8506000WVYG | 105 mm  | 125 mm | 1        | 4284   |

### TTF-YVYG

|                                 |                    |
|---------------------------------|--------------------|
| Material                        | PVC film (outdoor) |
| Colour                          | Yellow             |
| Thickness                       | 0.08 mm            |
| UV resistance                   | ****               |
| Min operating temperature range | -30 °C             |
| Max operating temperature range | 70 °C              |
| Min application temperature     | 10 °C              |
| Max application temperature     | 40 °C              |

| Type            | Width   | Length | Pack qty | SWcode |
|-----------------|---------|--------|----------|--------|
| TTF 8506012YVYG | 25.4 mm | 125 mm | 1        | 4287   |
| TTF 8506000YVYG | 105 mm  | 125 mm | 1        | 4284   |
| TTF 8506001YVYG | 80 mm   | 125 mm | 1        | 4282   |
| TTF 8506003YVYG | 35 mm   | 125 mm | 1        | 4280   |
| TTF 8506004YVYG | 40 mm   | 125 mm | 1        | 4281   |
| TTF 8506011YVYG | 50 mm   | 125 mm | 1        | 4283   |
| TTF 8506010YVYG | 58 mm   | 125 mm | 1        |        |

### TTF-SVYG

|                                 |                    |
|---------------------------------|--------------------|
| Colour                          | Metallic grey      |
| Material                        | PVC film (outdoor) |
| Thickness                       | 0.07 mm            |
| UV resistance                   | ****               |
| Min operating temperature range | -30 °C             |
| Max operating temperature range | 70 °C              |
| Min application temperature     | 10 °C              |
| Max application temperature     | 40 °C              |

| Type            | Width   | Length | Pack qty | SWcode |
|-----------------|---------|--------|----------|--------|
| TTF 8506012SVYG | 25.4 mm | 125 mm | 1        | 4287   |
| TTF 8506000SVYG | 105 mm  | 125 mm | 1        | 4284   |
| TTF 8506001SVYG | 80 mm   | 125 mm | 1        | 4282   |
| TTF 8506003SVYG | 35 mm   | 125 mm | 1        | 4280   |
| TTF 8506004SVYG | 40 mm   | 125 mm | 1        | 4281   |
| TTF 8506011SVYG | 50 mm   | 125 mm | 1        | 4283   |
| TTF 85060010VYG | 58 mm   | 125 mm | 1        |        |

## TTF-PPYG

|                                 |                |
|---------------------------------|----------------|
| Material                        | Polyester film |
| Colour                          | Metallic grey  |
| Thickness                       | 0.05 mm        |
| UV resistance                   | **             |
| Min operating temperature range | -40 °C         |
| Max operating temperature range | 140 °C         |
| Min application temperature     | 10 °C          |
| Max application temperature     | 40 °C          |

| Type            | Width   | Length | Pack qty | SWcode |
|-----------------|---------|--------|----------|--------|
| TTF 8506012PPYG | 25.4 mm | 125 mm | 1        | 4287   |
| TTF 8506000PPYG | 105 mm  | 125 mm | 1        | 4284   |
| TTF 8506001PPYG | 80 mm   | 125 mm | 1        | 4282   |
| TTF 8506003PPYG | 35 mm   | 125 mm | 1        | 4280   |
| TTF 8506004PPYG | 40 mm   | 125 mm | 1        | 4281   |
| TTF 8506011PPYG | 50 mm   | 125 mm | 1        | 4283   |
| TTF 8506010PPYG | 58 mm   | 125 mm | 1        |        |

## TTF-CPYG

|                                 |             |
|---------------------------------|-------------|
| Colour                          | Transparent |
| Material                        | PET         |
| Thickness                       | 0.02 mm     |
| UV resistance                   | ***         |
| Min operating temperature range | -40 °C      |
| Max operating temperature range | 125 °C      |
| Min application temperature     | 10 °C       |
| Max application temperature     | 40 °C       |

| Type            | Width   | Length | Pack qty | SWcode |
|-----------------|---------|--------|----------|--------|
| TTF 8506012CPYG | 25.4 mm | 125 m  | 1        | 4287   |
| TTF 8506000CPYG | 105 mm  | 125 m  | 1        | 4284   |
| TTF 8506001CPYG | 80 mm   | 125 m  | 1        | 4282   |
| TTF 8506003CPYG | 35 mm   | 125 m  | 1        | 4280   |
| TTF 8506004CPYG | 40 mm   | 125 m  | 1        | 4281   |
| TTF 8506010CPYG | 58 mm   | 125 m  | 1        | 4285   |
| TTF 8506011CPYG | 50 mm   | 125 m  | 1        | 4283   |

## TTF-WPYG

|                                 |                |
|---------------------------------|----------------|
| Colour                          | White          |
| Material                        | Polyester film |
| Thickness                       | 0.05 mm        |
| UV resistance                   | *              |
| Min operating temperature range | -40 °C         |
| Max operating temperature range | 140 °C         |
| Min application temperature     | 10 °C          |
| Max application temperature     | 40 °C          |

| Type            | Width   | Length | Pack qty | SWcode |
|-----------------|---------|--------|----------|--------|
| TTF 8506012WPYG | 25.4 mm | 125 mm | 1        | 4287   |
| TTF 8506000WPYG | 105 mm  | 125 mm | 1        | 4284   |
| TTF 8506001WPYG | 80 mm   | 125 mm | 1        | 4282   |
| TTF 8506003WPYG | 35 mm   | 125 mm | 1        | 4280   |
| TTF 8506004WPYG | 40 mm   | 125 mm | 1        | 4281   |
| TTF 8506010WPYG | 58 mm   | 125 mm | 1        |        |
| TTF 8506011WPYG | 50 mm   | 125 mm | 1        | 4283   |

## TTF-WCYG/5

|                                 |                     |
|---------------------------------|---------------------|
| Colour                          | White               |
| Material                        | PVC film reflective |
| Thickness                       | 0.08 mm             |
| UV resistance                   | ****                |
| Min operating temperature range | -30 °C              |
| Max operating temperature range | 70 °C               |
| Min application temperature     | 10 °C               |
| Max application temperature     | 40 °C               |

| Type             | Width  | Length | Pack qty | SWcode |
|------------------|--------|--------|----------|--------|
| TTF 856007WCYG/5 | 35 mm  | 24 m   | 1        | 4280   |
| TTF 856008WCYG/5 | 80 mm  | 24 m   | 1        | 4282   |
| TTF 856006WCYG/5 | 105 mm | 24 m   | 1        | 4284   |

## TTF-YCYG/5

|                                 |                     |
|---------------------------------|---------------------|
| Colour                          | Yellow              |
| Material                        | PVC film reflective |
| Thickness                       | 0.08 mm             |
| UV resistance                   | ****                |
| Min operating temperature range | -30 °C              |
| Max operating temperature range | 70 °C               |
| Max application temperature     | 40 °C               |
| Min application temperature     | 10 °C               |

| Type             | Width  | Pack qty | SWcode | Length |
|------------------|--------|----------|--------|--------|
| TTF 856007YCYG/5 | 35 mm  | 1        | 4280   | 24 m   |
| TTF 856008YCYG/5 | 80 mm  | 1        | 4282   | 24 m   |
| TTF 856006YCYG/5 | 105 mm | 1        | 4284   | 24 m   |

### TTF-BCYG/5

|                                 |                     |
|---------------------------------|---------------------|
| Colour                          | Blue                |
| Material                        | PVC film reflective |
| Thickness                       | 0.08 mm             |
| UV resistance                   | ****                |
| Min operating temperature range | -30 °C              |
| Max operating temperature range | 70 °C               |
| Min application temperature     | 10 °C               |
| Max application temperature     | 40 °C               |

| Type             | Width  | Pack qty | SWcode |
|------------------|--------|----------|--------|
| TTF 856009BCYG/5 | 115 mm | 1        | 4286   |

### TTF-WVRG

|                                 |           |
|---------------------------------|-----------|
| Colour                          | White     |
| Material                        | Rigid PVC |
| Thickness                       | 0.4 mm    |
| Min operating temperature range | -30 °C    |
| Max operating temperature range | 70 °C     |

| Type            | Width  | Pack qty | Length |
|-----------------|--------|----------|--------|
| TTF 8506002WVRG | 100 mm | 1        | 25 m   |

### TTF-YVRG

|                                 |           |
|---------------------------------|-----------|
| Colour                          | Yellow    |
| Material                        | Rigid PVC |
| Thickness                       | 0.4 mm    |
| Min operating temperature range | -30 °C    |
| Max operating temperature range | 70 °C     |

| Type            | Width  | Pack qty | Length |
|-----------------|--------|----------|--------|
| TTF 8506002YVRG | 100 mm | 1        | 25 m   |