

WRAPAROUND CABLE MARKERS KM

self adhesive, self laminating, square corners, precut

KM05025 wraparound cable markers hand-printing with permanent pens (see p. 70), are suitable for identifying large diameter cables, tubes and conduit. The procedure is quick - carefully hand print on the markable coloured area then wrap the marker around the cable/tube overlapping the clear part onto the marked area to protect it from water, alcohol, dust, and chemical and atmospheric agents. The fixing margin is important as it protects the marking from contamination by the hands. Many types of marking media can be used including pencil, ballpoint pen, marker pen, etc.



CERTIFICATES 



2011/65/EU

WRAPAROUND CABLE MARKERS **KM**

Technical characteristics

Min operating temperature range	-30 °C
Max operating temperature range	140 °C
Min application temperature	10 °C
Max application temperature	40 °C
Material	Soft PVC film



WRAPAROUND CABLE MARKERS KM

List of products

KM05025

Type	Length	Height of the writing	Width of the writing	Minimum outside diameter	Maximum outside diameter	Pack qty	Colour
KM 05025 189109	50 mm	15 mm	25 mm	6 mm	10 mm	90	White
KM 05025 184109	50 mm	15 mm	25 mm	6 mm	10 mm	90	Yellow
KM 05025 183109	50 mm	15 mm	25 mm	6 mm	10 mm	90	Orange
KM 05025 182109	50 mm	15 mm	25 mm	6 mm	10 mm	90	Red
KM 05025 186109	50 mm	15 mm	25 mm	6 mm	10 mm	90	Blue

KM07525

Type	Length	Height of the writing	Width of the writing	Minimum outside diameter	Maximum outside diameter	Pack qty	Colour
KM 07525 189115	75 mm	25 mm	25 mm	8 mm	14 mm	60	White
KM 07525 184115	75 mm	25 mm	25 mm	8 mm	14 mm	60	Yellow

KM15025

Type	Length	Height of the writing	Width of the writing	Minimum outside diameter	Maximum outside diameter	Pack qty	Colour
KM 15025 189123	150 mm	25 mm	25 mm	20 mm	38 mm	30	White
KM 15025 184123	150 mm	25 mm	25 mm	20 mm	38 mm	30	Yellow
KM 15025 183123	150 mm	25 mm	25 mm	20 mm	38 mm	30	Orange
KM 15025 182123	150 mm	25 mm	25 mm	20 mm	38 mm	30	Red
KM 15025 186123	150 mm	25 mm	25 mm	20 mm	38 mm	30	Blue
KM 15025 185123	150 mm	25 mm	25 mm	20 mm	38 mm	30	Green