


CABLE TIES G

Ideal for securing tie-on tags, labels and holders to electrical wiring, pipes and conduit. Black ties have a higher UV resistance due to increased Carbon black loading. G series ties offer rapid installation due to the low friction coefficient of the material and have an angled tongue to facilitate easy introduction into the buckle. Rounded corners for increased safety.




CERTIFICATES 

 2011/65/EU

CABLE TIES G

Technical characteristics

Min operating temperature range	-40 °C
Max operating temperature range	85 °C
Min operating temperature range (surge)	-40 °C
Max operating temperature range (surge)	120 °C
UL94 class	V2
Material	Polyamide PA6.6



CABLE TIES G

List of products

G


Type	A	L	Maximum outside diameter	Pack qty	Minimum loop tensile strenght	Colour
G80X2.4	2.4 mm	80 mm	15 mm	100	8 kg	Natural
G80X2.4/M	2.4 mm	80 mm	15 mm	1,000	8 kg	Natural
G90X2.4	2.4 mm	90 mm	16 mm	100	8 kg	Natural
G100X2.5	2.5 mm	100 mm	22 mm	100	8 kg	Natural
G100X2.5/M	2.5 mm	100 mm	22 mm	1,000	8 kg	Natural
G120X2.5	2.5 mm	120 mm	30 mm	100	8 kg	Natural
G140X2.5	2.5 mm	140 mm	33 mm	100	8 kg	Natural
G140X2.5/M	2.5 mm	140 mm	33 mm	1,000	8 kg	Natural
G160X2.5	2.5 mm	160 mm	40 mm	100	8 kg	Natural
G160X2.5/M	2.5 mm	160 mm	40 mm	1,000	8 kg	Natural
G200X2.5	2.5 mm	200 mm	53 mm	100	8 kg	Natural
G200X2.5/M	2.5 mm	200 mm	53 mm	1,000	8 kg	Natural
G250X2.8	2.8 mm	250 mm	65 mm	100	14 kg	Natural
G300X2.8	2.8 mm	300 mm	76 mm	100	14 kg	Natural
G120X3.6	3.6 mm	120 mm	30 mm	100	18 kg	Natural
G140X3.6	3.6 mm	140 mm	33 mm	100	18 kg	Natural
G140X3.6/M	3.6 mm	140 mm	33 mm	1,000	18 kg	Natural
G150X3.6	3.6 mm	150 mm	35 mm	100	18 kg	Natural
G180X3.6	3.6 mm	180 mm	44 mm	100	18 kg	Natural
G200X3.6	3.6 mm	200 mm	53 mm	100	18 kg	Natural
G200X3.6/M	3.6 mm	200 mm	53 mm	1,000	18 kg	Natural
G250X3.6	3.6 mm	250 mm	65 mm	100	18 kg	Natural
G300X3.6	3.6 mm	300 mm	76 mm	100	18 kg	Natural
G300X3.6/M	3.6 mm	300 mm	76 mm	1,000	18 kg	Natural
G370X3.6	3.6 mm	370 mm	102 mm	100	18 kg	Natural
G120X4.8	4.8 mm	120 mm	24 mm	100	22 kg	Natural

G160X4.8	4.8 mm	160 mm	38 mm	100	22 kg	Natural
G190X4.8	4.8 mm	190 mm	46 mm	100	22 kg	Natural
G190X4.8/M	4.8 mm	190 mm	46 mm	1,000	22 kg	Natural
G200X4.8	4.8 mm	200 mm	50 mm	100	22 kg	Natural
G200X4.8/M	4.8 mm	200 mm	50 mm	1,000	22 kg	Natural
G250X4.8/M	4.8 mm	250 mm	60 mm	1,000	22 kg	Natural
G250X4.8	4.8 mm	250 mm	60 mm	100	22 kg	Natural
G280X4.8	4.8 mm	280 mm	70 mm	100	22 kg	Natural
G300X4.8	4.8 mm	300 mm	76 mm	100	22 kg	Natural
G370X4.8	4.8 mm	370 mm	102 mm	100	22 kg	Natural
G390X4.8	4.8 mm	390 mm	105 mm	100	22 kg	Natural
G430X4.8	4.8 mm	430 mm	110 mm	100	22 kg	Natural
G450X4.8	4.8 mm	450 mm	116 mm	100	22 kg	Natural
G530X4.8	4.8 mm	530 mm	140 mm	100	22 kg	Natural
G80X2.4N	2.4 mm	80 mm	15 mm	100	8 kg	Black
G80X2.4N/M	2.4 mm	80 mm	15 mm	1,000	8 kg	Black
G90X2.4N	2.4 mm	90 mm	16 mm	100	8 kg	Black
G100X2.5N	2.5 mm	100 mm	22 mm	100	8 kg	Black
G100X2.5N/M	2.5 mm	100 mm	22 mm	1,000	8 kg	Black
G120X2.5N	2.5 mm	120 mm	30 mm	100	8 kg	Black
G140X2.5N	2.5 mm	140 mm	33 mm	100	8 kg	Black
G140X2.5N/M	2.5 mm	140 mm	33 mm	1,000	8 kg	Black
G160X2.5N	2.5 mm	160 mm	40 mm	100	8 kg	Black
G160X2.5N/M	2.5 mm	160 mm	40 mm	1,000	8 kg	Black
G200X2.5N	2.5 mm	200 mm	53 mm	100	8 kg	Black
G200X2.5N/M	2.5 mm	200 mm	53 mm	1,000	8 kg	Black
G250X2.8N	2.8 mm	250 mm	65 mm	100	14 kg	Black
G300X2.8N	2.8 mm	300 mm	76 mm	100	14 kg	Black
G120X3.6N	3.6 mm	120 mm	30 mm	100	18 kg	Black
G140X3.6N	3.6 mm	140 mm	33 mm	100	18 kg	Black
G140X3.6N/M	3.6 mm	140 mm	33 mm	1,000	18 kg	Black
G150X3.6N	3.6 mm	150 mm	35 mm	100	18 kg	Black
G180X3.6N	3.6 mm	180 mm	44 mm	100	18 kg	Black
G200X3.6N	3.6 mm	200 mm	53 mm	100	18 kg	Black
G200X3.6N/M	3.6 mm	200 mm	53 mm	1,000	18 kg	Black

G250X3.6N	3.6 mm	250 mm	65 mm	100	18 kg	Black
G300X3.6N	3.6 mm	300 mm	76 mm	100	18 kg	Black
G300X3.6N/M	3.6 mm	300 mm	76 mm	1,000	18 kg	Black
G370X3.6N	3.6 mm	370 mm	102 mm	100	18 kg	Black
G120X4.8N	4.8 mm	120 mm	24 mm	100	22 kg	Black
G160X4.8N	4.8 mm	160 mm	38 mm	100	22 kg	Black
G190X4.8N	4.8 mm	190 mm	46 mm	100	22 kg	Black
G190X4.8N/M	4.8 mm	190 mm	46 mm	1,000	22 kg	Black
G200X4.8N	4.8 mm	200 mm	50 mm	100	22 kg	Black
G200X4.8N/M	4.8 mm	200 mm	50 mm	1,000	22 kg	Black
G250X4.8N/M	4.8 mm	250 mm	60 mm	1,000	22 kg	Black
G250X4.8N	4.8 mm	250 mm	60 mm	100	22 kg	Black
G280X4.8N	4.8 mm	280 mm	70 mm	100	22 kg	Black
G300X4.8N	4.8 mm	300 mm	76 mm	100	22 kg	Black
G370X4.8N	4.8 mm	370 mm	102 mm	100	22 kg	Black
G390X4.8N	4.8 mm	390 mm	105 mm	100	22 kg	Black
G430X4.8N	4.8 mm	430 mm	110 mm	100	22 kg	Black
G450X4.8N	4.8 mm	450 mm	116 mm	100	22 kg	Black
G53X4.8N	4.8 mm	530 mm	140 mm	100	22 kg	Black
G150X7.6	7.6 mm	150 mm	33 mm	100	55 kg	Natural
G200X7.6	7.6 mm	200 mm	50 mm	100	55 kg	Natural
G250X7.6	7.6 mm	250 mm	65 mm	100	55 kg	Natural
G300X7.6	7.6 mm	300 mm	76 mm	100	55 kg	Natural
G370X7.6	7.6 mm	370 mm	102 mm	100	55 kg	Natural
G430X7.6	7.6 mm	430 mm	125 mm	100	55 kg	Natural
G530X7.6	7.6 mm	530 mm	140 mm	100	55 kg	Natural
G150X7.6N	7.6 mm	150 mm	33 mm	100	55 kg	Black
G200X7.6N	7.6 mm	200 mm	50 mm	100	55 kg	Black
G250X7.6N	7.6 mm	250 mm	65 mm	100	55 kg	Black
G300X7.6N	7.6 mm	300 mm	76 mm	100	55 kg	Black
G370X7.6N	7.6 mm	370 mm	102 mm	100	55 kg	Black
G430X7.6N	7.6 mm	430 mm	125 mm	100	55 kg	Black
G530X7.6N	7.6 mm	530 mm	140 mm	100	55 kg	Black
G430X9.0	9 mm	430 mm	110 mm	100	80 kg	Natural
G530X9.0	9 mm	530 mm	140 mm	100	80 kg	Natural

G710X9.0	9 mm	710 mm	190 mm	100	80 kg	Natural
G780X9.0	9 mm	780 mm	228 mm	100	80 kg	Natural
G830X9.0	9 mm	830 mm	239 mm	100	80 kg	Natural
G920X9.0	9 mm	920 mm	263 mm	100	80 kg	Natural
G1020X9.0	9 mm	1020 mm	295 mm	100	80 kg	Natural
G1220X9.0	9 mm	1220 mm	365 mm	100	80 kg	Natural
G430X9.0N	9 mm	430 mm	110 mm	100	80 kg	Black
G530X9.0N	9 mm	530 mm	140 mm	100	80 kg	Black
G710X9.0N	9 mm	710 mm	190 mm	100	80 kg	Black
G780X9.0N	9 mm	780 mm	228 mm	100	80 kg	Black
G830X9.0N	9 mm	830 mm	239 mm	100	80 kg	Black
G920X9.0N	9 mm	920 mm	263 mm	100	80 kg	Black
G1020X9.0N	9 mm	1020 mm	295 mm	100	80 kg	Black
G1220X9.0N	9 mm	1220 mm	365 mm	100	80 kg	Black
G230X12.6	12.6 mm	230 mm	50 mm	100	115 kg	Natural
G380X12.6	12.6 mm	380 mm	106 mm	100	115 kg	Natural
G480X12.6	12.6 mm	480 mm	120 mm	100	115 kg	Natural
G580X12.6	12.6 mm	580 mm	152 mm	100	115 kg	Natural
G730X12.6	12.6 mm	730 mm	204 mm	100	115 kg	Natural
G880X12.6	12.6 mm	880 mm	248 mm	100	115 kg	Natural
G1030X12.6	12.6 mm	1030 mm	295 mm	100	115 kg	Natural
G230X12.6N	12.6 mm	230 mm	50 mm	100	115 kg	Black
G380X12.6N	12.6 mm	380 mm	106 mm	100	115 kg	Black
G480X12.6N	12.6 mm	480 mm	120 mm	100	115 kg	Black
G580X12.6N	12.6 mm	580 mm	152 mm	100	115 kg	Black
G730X12.6N	12.6 mm	730 mm	204 mm	100	115 kg	Black
G880X12.6N	12.6 mm	880 mm	248 mm	100	115 kg	Black
G1030X12.6N	12.6 mm	1030 mm	295 mm	100	115 kg	Black
G530X4.8N	4.8 mm	530 mm	140 mm	100	22 kg	Natural

Used with tie

Tags

CABLE AND CONDUIT TAGS MG-ETF - CABLE AND CONDUIT TAGS MG-ETF

LAMINATED WRITE-ON TIE-ON TAGS MS-ETF - LAMINATED WRITE-ON TIE-ON TAGS MS-ETF

DOG TAGS MG-DOG-HF

MG-DOG 40205-HF	MG-DOG 40206-HF	MG-DOG 48300-HF
MG-DOG 48340-HF		

MG-DOG.

MG-DOG 48203	MG-DOG 48204	MG-DOG 48244
MG-DOG 48300	MG-DOG 48320	MG-DOG 48322
MG-DOG 48340	MG-DOG 48341	MG-DOG 48342
MG-DOG 48352	MG-DOG 48391	MG-DOG 48392

Holders

TRANSPARENT HOLDERS PM-DT - TRANSPARENT HOLDERS PM-DT

TRANSPARENT HOLDERS PMT-CT - PMT-CT 54015

TRANSPARENT HOLDERS PMT-ET - PMT-ET 54000

TRANSPARENT HOLDERS PM-ET - TRANSPARENT HOLDERS PM-ET

TRANSPARENT HOLDERS PMT-DT

PMT-DT 60002	PMT-DT 60042
--------------	--------------

Tags reel

CABLE AND CONDUIT TAGS ETF-ROLL - CABLE AND CONDUIT TAGS ETF-ROLL

Pre-printed

ACCESSORIES FMH - ACCESSORIES FMH

Products used together

Tools

CABLE TIE TOOL 55230 - 5523036090