


CABLE TIES G V0




CERTIFICATES 

 2011/65/EU

CABLE TIES G V0

Technical characteristics

Min operating temperature range	-40 °C
Max operating temperature range	85 °C
Min operating temperature range (surge)	-40 °C
Max operating temperature range (surge)	120 °C
UL94 class	V0
Material	Polyamide PA6.6



CABLE TIES G V0

List of products

G V0



Type	A	L	Maximum outside diameter	Pack qty	Min. pack qty	Minimum loop tensile strenght	Colour
G90X2.4 V0	2.4 mm	90 mm	16 mm	100	1,000	8 kg	Natural
G100X2.5/M V0	2.5 mm	100 mm	22 mm	1,000	1,000	8 kg	Natural
G140X2.5/M V0	2.5 mm	140 mm	33 mm	1,000	1,000	8 kg	Natural
G200X2.5/M V0	2.5 mm	200 mm	53 mm	1,000	1,000	8 kg	Natural
G150X3.6 V0	3.6 mm	150 mm	35 mm	100	1,000	18 kg	Natural
G200X4.8/M V0	4.8 mm	200 mm	50 mm	1,000	1,000	22 kg	Natural
G370X4.8 V0	4.8 mm	370 mm	102 mm	100	100	22 kg	Natural
G430X4.8 V0	4.8 mm	430 mm	110 mm	100	100	22 kg	Natural
G710X9.0 V0	9 mm	710 mm	190 mm	100	100	80 kg	Natural

Used with tie

Tags

CABLE AND CONDUIT TAGS MG-ETF - CABLE AND CONDUIT TAGS MG-ETF

LAMINATED WRITE-ON TIE-ON TAGS MS-ETF - LAMINATED WRITE-ON TIE-ON TAGS MS-ETF

DOG TAGS MG-DOG-HF

MG-DOG 40205-HF	MG-DOG 40206-HF	MG-DOG 48300-HF
MG-DOG 48340-HF		

MG-DOG.

MG-DOG 48203	MG-DOG 48204	MG-DOG 48244
MG-DOG 48300	MG-DOG 48320	MG-DOG 48322
MG-DOG 48340	MG-DOG 48341	MG-DOG 48342
MG-DOG 48352	MG-DOG 48391	MG-DOG 48392

HOLDERS

TRANSPARENT HOLDERS PM-DT - TRANSPARENT HOLDERS PM-DT

TRANSPARENT HOLDERS PMF-ET - TRANSPARENT HOLDERS PMF-ET

TRANSPARENT HOLDERS PMT-ET - PMT-ET 54000

TRANSPARENT HOLDERS PM-ET - TRANSPARENT HOLDERS PM-ET

TRANSPARENT HOLDERS PMT-DT

PMT-DT 60002	PMT-DT 60042
--------------	--------------

Tags reel

CABLE AND CONDUIT TAGS ETF-ROLL - CABLE AND CONDUIT TAGS ETF-ROLL

Pre-printed

ACCESSORIES FMH - ACCESSORIES FMH

Products used together

Tools

CABLE TIE TOOL 55230 - 5523036090