

## CABLE TIES GX

### *in Stainless Steel AISI 304*

Unique ball locking mechanism that allows simple and rapid installation and secure locking. High tensile strength. Non-flammability. High resistance to acetic acid, alkalies, sulphuric acid, corrosion, etc. In general very resistant to most hostile environments.



---

CERTIFICATES 




2011/65/EU

# CABLE TIES GX

## *Technical characteristics*

Min operating temperature range	-80 °C
Max operating temperature range	500 °C
Material	Stainless steel AISI 304



# CABLE TIES GX

## List of products

### GX



Type	A	L	Maximum outside diameter	Pack qty	Minimum loop tensile strenght
GX200X4.5	4.5 mm	200 mm	50 mm	100	46 kg
GX300X4.5	4.5 mm	300 mm	76 mm	100	46 kg
GX370X4.5	4.5 mm	370 mm	102 mm	100	46 kg
GX520X4.5	4.5 mm	520 mm	156 mm	100	46 kg
GX370X7.9	7.9 mm	370 mm	102 mm	100	114 kg
GX680X7.9	7.9 mm	680 mm	207 mm	100	114 kg
GX1020X7.9	7.9 mm	1020 mm	312 mm	100	114 kg

## Products used together

### Tools

**CABLE TIE TOOL 55270 - 5527030079**