

BUTT CONNECTORS WL-M

PE HD insulated, heat shrinkable

Manufactured from copper tube
Electrolytically tin plated



CERTIFICATES 



2011/65/EU

BUTT CONNECTORS WL-M

Technical characteristics


Dimensional form	Butt
Min operating temperature range	-40 °C
Max operating temperature range	105 °C
Min shrinkage ratio temperature	150 °C
Halogen Free	yes
Material (Body)	ETP Copper electrolytically tinned
Material (Insulated)	PE-HD
IP protection	68




BUTT CONNECTORS WL-M

List of products


WL-M Cable type: copper, Minimum section: 0.5 mm², Maximum section: 1 mm²

Type	Impulse voltage	Colour	Maximum diameter of the stripped cable	L1	L2	Pack qty	Min. pack qty	
WL03-M	600 V	Red	1.7 mm	15 mm	36 mm	1,500	100	


WL-M Cable type: flexible copper, Minimum section: 0.5 mm², Maximum section: 1 mm²

Type	Impulse voltage	Colour	Maximum diameter of the stripped cable	L1	L2	Pack qty	Min. pack qty	
WL03-M	600 V	Red	1.7 mm	15 mm	36 mm	1,500	100	


WL-M Cable type: copper, Minimum section: 1.5 mm², Maximum section: 2.5 mm²

Type	Impulse voltage	Colour	Maximum diameter of the stripped cable	L1	L2	Pack qty	Min. pack qty	
WL06-M	600 V	Blue	2.3 mm	15 mm	36 mm	1,000	100	

WL-M Cable type: flexible copper, Minimum section: 1.5 mm², Maximum section: 2.5 mm²

Type	Impulse voltage	Colour	Maximum diameter of the stripped cable	L1	L2	Pack qty	Min. pack qty	
WL06-M	600 V	Blue	2.3 mm	15 mm	36 mm	1,000	100	

WL-M Cable type: flexible copper, Minimum section: 4 mm², Maximum section: 6 mm²

Type	Impulse voltage	Colour	Maximum diameter of the stripped cable	L1	L2	Pack qty	Min. pack qty	
WL1-M	600 V	Yellow	3.4 mm	15 mm	41 mm	500	100	

WL-M Cable type: copper, Minimum section: 4 mm², Maximum section: 6 mm²

Type	Impulse voltage	Colour	Maximum diameter of the stripped cable	L1	L2	Pack qty	Min. pack qty	
WL1-M	600 V	Yellow	3.4 mm	15 mm	41 mm	500	100	