

## BUTT CONNECTORS WL-M

*PE HD insulated, heat shrinkable*

Manufactured from copper tube  
Electrolytically tin plated  
The connectors are manufactured from electrolytic Copper Cu-ETP CWO04A according to UNI EN 13600 and are tin plated with a minimum thickness of 3µm.



CERTIFICATES 



2011/65/EU

## BUTT CONNECTORS WL-M


### *Technical characteristics*


Dimensional form	Butt
Min operating temperature range	-40 °C
Max operating temperature range	105 °C
Min shrinkage ratio temperature	150 °C
Halogen Free	yes
Material (Body)	ETP Copper electrolytically tinned
Material (Insulated)	PE-HD
IP protection	68





## BUTT CONNECTORS WL-M


### List of products

<b>WL-M</b> Cable type: copper, Minimum section: 0.25 mm <sup>2</sup> , Maximum section: 1.5 mm <sup>2</sup>							
Type	Impulse voltage	Colour	L1	L2	Pack qty	Min. pack qty	
WL03-M	600 V	Red	15 mm	36 mm	1,500	100	

<b>WL-M</b> Cable type: flexible copper, Minimum section: 0.25 mm <sup>2</sup> , Maximum section: 1.5 mm <sup>2</sup>							
Type	Impulse voltage	Colour	L1	L2	Pack qty	Min. pack qty	
WL03-M	600 V	Red	15 mm	36 mm	1,500	100	

<b>WL-M</b> Cable type: copper, Minimum section: 1.5 mm <sup>2</sup> , Maximum section: 2.5 mm <sup>2</sup>							
Type	Impulse voltage	Colour	L1	L2	Pack qty	Min. pack qty	
WL06-M	600 V	Blue	15 mm	36 mm	1,000	100	

<b>WL-M</b> Cable type: flexible copper, Minimum section: 1.5 mm <sup>2</sup> , Maximum section: 2.5 mm <sup>2</sup>							
Type	Impulse voltage	Colour	L1	L2	Pack qty	Min. pack qty	
WL06-M	600 V	Blue	15 mm	36 mm	1,000	100	

<b>WL-M</b> Cable type: flexible copper, Minimum section: 4 mm <sup>2</sup> , Maximum section: 6 mm <sup>2</sup>							
Type	Impulse voltage	Colour	L1	L2	Pack qty	Min. pack qty	
WL1-M	600 V	Yellow	15 mm	41 mm	500	100	

<b>WL-M</b> Cable type: copper, Minimum section: 4 mm <sup>2</sup> , Maximum section: 6 mm <sup>2</sup>							
Type	Impulse voltage	Colour	L1	L2	Pack qty	Min. pack qty	
WL1-M	600 V	Yellow	15 mm	41 mm	500	100	