

# INSULATED CHAIN TERMINALS CP-F

## *female disconnect terminals*

The “CP” range of terminals has been designed to meet the increasing demands for improved safety and reliability of electrical connectors.

Developed for use with production equipment, to give a quick and reliable crimped joint, the polycarbonate insulation is a halogen free, self extinguishing thermoplastic material class V0 (UL 94).

The unique funnel shaped entry of the insulation sleeve guarantees total insertion of the conductor strands into the terminal barrel, creating a secure and reliable, electrical and mechanical connection.



## Technical details

The connectors are manufactured from electrolytic Copper Cu-ETP CWO04A according to UNI EN 1652:1999 and are tin plated with a minimum thickness of 3µm.

Main characteristics of the PC sleeves:

- > DIELECTRIC STRENGTH (KV/mm): > 30
- > VOLUME RESISTIVITY (Ω/cm): >1016
- > MAX OPERATING TEMPERATURE (°C): 115-130
- > FLAMMABILITY (UL-94): V0
- > DENSITY (g/cm<sup>3</sup>): 1,2
- > WATER ABSORPTION (%): 0,15
- > BREAKING LOAD (N/mm<sup>2</sup>): > 65



The connectors can be stored at a minimum temperature not below - 40°C.


## Markings

**cULus** According to UL486A standard (file E212000 and E125401)

Certified according to **EN 45545-2:2013** for Hazard Levels HL1 - HL2, requirement set R22 and for Hazard Levels HL1 - HL2 - HL3, requirement set R23

CERTIFICATES 

 According to UL 486A standard (file E125401)  According to UL 486A standard (file E212000)


 2011/65/EU



# INSULATED CHAIN TERMINALS CP-F

## *Technical characteristics*


Easy entry	yes
Halogen Free	yes
UL94 class	V0
Min operating temperature range	-20 °C
Max operating temperature range	115 °C
Max operating temperature range (surge)	130 °C
Dimensional form	Female terminal
Material (Body)	Electrolytically tin-plated brass
Material (Partially reinforced)	ETP Copper electrolytically tinned
Material (Partially reinforced)	Polycarbonate



# INSULATED CHAIN TERMINALS CP-F


## List of products

### CRP-F *Cable type: flexible copper, Minimum section: 0.25 mm<sup>2</sup>, Maximum section: 1.5 mm<sup>2</sup>*



Type	Colour	Width	Length	Height of the hooked	Pack qty
CRP-F305	Red	2.8 mm	20 mm	0.5 mm	2,000
CRP-F308	Red	2.8 mm	20 mm	0.8 mm	2,000
CRP-F405	Red	4.8 mm	20 mm	0.5 mm	2,000
CRP-F408	Red	4.8 mm	20 mm	0.8 mm	2,000
CRP-F608	Red	6.35 mm	22.7 mm	0.8 mm	2,000

### CRP-F *Cable type: copper, Minimum section: 0.25 mm<sup>2</sup>, Maximum section: 1.5 mm<sup>2</sup>*




Type	Colour	Width	Length	Height of the hooked	Pack qty
CRP-F305	Red	2.8 mm	20 mm	0.5 mm	2,000
CRP-F308	Red	2.8 mm	20 mm	0.8 mm	2,000
CRP-F405	Red	4.8 mm	20 mm	0.5 mm	2,000
CRP-F408	Red	4.8 mm	20 mm	0.8 mm	2,000
CRP-F608	Red	6.35 mm	22.7 mm	0.8 mm	2,000


### CBP-F *Cable type: copper, Minimum section: 1.5 mm<sup>2</sup>, Maximum section: 2.5 mm<sup>2</sup>*




Type	Colour	Width	Length	Height of the hooked	Pack qty
CBP-F405	Blue	4.8 mm	20.1 mm	0.5 mm	1,750
CBP-F408	Blue	4.8 mm	20.1 mm	0.8 mm	1,750
CBP-F608	Blue	6.35 mm	22.8 mm	0.8 mm	1,750

**CBP-F** Cable type: flexible copper, Minimum section: 1.5 mm<sup>2</sup>, Maximum section: 2.5 mm<sup>2</sup>


Type	Colour	Width	Length	Height of the hooked	Pack qty
CBP-F405	Blue	4.8 mm	20.1 mm	0.5 mm	1,750
CBP-F408	Blue	4.8 mm	20.1 mm	0.8 mm	1,750
CBP-F608	Blue	6.35 mm	22.8 mm	0.8 mm	1,750

**CGP-F** Cable type: flexible copper, Minimum section: 4 mm<sup>2</sup>, Maximum section: 6 mm<sup>2</sup>


Type	Colour	Width	Length	Height of the hooked	Pack qty
CGP-F608	Yellow	6.35 mm	25.7 mm	0.8 mm	1,250

**CGP-F** Cable type: copper, Minimum section: 4 mm<sup>2</sup>, Maximum section: 6 mm<sup>2</sup>


Type	Colour	Width	Length	Height of the hooked	Pack qty
CGP-F608	Yellow	6.35 mm	25.7 mm	0.8 mm	1,250