


## PARALLEL CONNECTORS L-P

Made of electrolytic copper tube Cu-ETP CWO04A conform to UNI EN 13600, having the same dimensions as A-M series lugs, L-P connectors are annealed and electrolytically tin plated (minimum thickness of 3µm). They feature an internal taper to ease the introduction of the conductor.



CERTIFICATES 

 2011/65/EU

## PARALLEL CONNECTORS L-P


### *Technical characteristics*

Max operating temperature range

180 °C

Material

ETP Copper electrolytically tinned



# PARALLEL CONNECTORS L-P


## List of products

**L-P** Cable type: copper, Maximum section: 10 mm<sup>2</sup>



Type	Øi	L	Pack qty	Min. pack qty
L2-P	4.6 mm	10.5 mm	3,000	100

**L-P** Cable type: flexible copper, Maximum section: 10 mm<sup>2</sup>



Type	Øi	L	Pack qty	Min. pack qty
L2-P	4.6 mm	10.5 mm	3,000	100

**L-P** Cable type: copper, Maximum section: 16 mm<sup>2</sup>




Type	Øi	L	Pack qty	Min. pack qty
L3-P	5.8 mm	11.5 mm	2,000	100

**L-P** Cable type: flexible copper, Maximum section: 16 mm<sup>2</sup>



Type	Øi	L	Pack qty	Min. pack qty
L3-P	5.8 mm	11.5 mm	2,000	100

**L-P** Cable type: copper, Maximum section: 25 mm<sup>2</sup>


Type	Øi	L	Pack qty	Min. pack qty
L5-P	7 mm	13 mm	1,500	100

**L-P** Cable type: flexible copper, Maximum section: 25 mm<sup>2</sup>


Type	Øi	L	Pack qty	Min. pack qty
L5-P	7 mm	13 mm	1,500	100

**L-P** Cable type: copper, Maximum section: 35 mm<sup>2</sup>


Type	Øi	L	Pack qty	Min. pack qty
L7-P	8.9 mm	14 mm	500	100

**L-P** Cable type: copper, Maximum section: 50 mm<sup>2</sup>


Type	Øi	L	Pack qty	Min. pack qty
L10-P	10 mm	16 mm	500	100

**L-P** Cable type: copper, Maximum section: 70 mm<sup>2</sup>


Type	Øi	L	Pack qty	Min. pack qty
L14-P	11.3 mm	18 mm	500	100

**L-P** Cable type: copper, Maximum section: 95 mm<sup>2</sup>


Type	Øi	L	Pack qty	Min. pack qty
L19-P	13.5 mm	19 mm	300	50

**L-P** Cable type: copper, Maximum section: 120 mm<sup>2</sup>


Type	Øi	L	Pack qty	Min. pack qty
L24-P	15.2 mm	22 mm	200	50

**L-P** Cable type: copper, Maximum section: 150 mm<sup>2</sup>


Type	Øi	L	Pack qty	Min. pack qty
L30-P	16.7 mm	26.5 mm	100	50

**L-P** Cable type: copper, Maximum section: 185 mm<sup>2</sup>


Type	Øi	L	Pack qty	Min. pack qty
L37-P	19.2 mm	26.5 mm	100	50

**L-P** Cable type: copper, Maximum section: 240 mm<sup>2</sup>


Type	Øi	L	Pack qty	Min. pack qty
L48-P	21.1 mm	34 mm	60	15

**L-P** Cable type: copper, Maximum section: 300 mm<sup>2</sup>


Type	Øi	L	Pack qty	Min. pack qty
L60-P	23.7 mm	43 mm	50	25

**L-P** Cable type: flexible copper, Minimum section: 0.25 mm<sup>2</sup>, Maximum section: 1.5 mm<sup>2</sup>


Type	Øi	L	Pack qty	Min. pack qty
L03-P	1.8 mm	6 mm	10,000	100

**L-P** Cable type: copper, Minimum section: 0.25 mm<sup>2</sup>, Maximum section: 1.5 mm<sup>2</sup>


Type	Øi	L	Pack qty	Min. pack qty
L03-P	1.8 mm	6 mm	10,000	100

**L-P** Cable type: copper, Minimum section: 1.5 mm<sup>2</sup>, Maximum section: 2.5 mm<sup>2</sup>


Type	Øi	L	Pack qty	Min. pack qty
L06-P	2.4 mm	6 mm	5,000	100

**L-P** Cable type: flexible copper, Minimum section: 1.5 mm<sup>2</sup>, Maximum section: 2.5 mm<sup>2</sup>


Type	Øi	L	Pack qty	Min. pack qty
L06-P	2.4 mm	6 mm	5,000	100

**L-P** Cable type: flexible copper, Minimum section: 4 mm<sup>2</sup>, Maximum section: 6 mm<sup>2</sup>



Type	Øi	L	Pack qty	Min. pack qty
L1-P	3.6 mm	9 mm	5,000	100

**L-P** Cable type: copper, Minimum section: 4 mm<sup>2</sup>, Maximum section: 6 mm<sup>2</sup>



Type	Øi	L	Pack qty	Min. pack qty
L1-P	3.6 mm	9 mm	5,000	100

**L-P** Cable type: flexible copper, Minimum section: 25 mm<sup>2</sup>, Maximum section: 35 mm<sup>2</sup>



Type	Øi	L	Pack qty	Min. pack qty
L7-P	8.9 mm	14 mm	500	100

**L-P** Cable type: flexible copper, Minimum section: 35 mm<sup>2</sup>, Maximum section: 50 mm<sup>2</sup>



Type	Øi	L	Pack qty	Min. pack qty
L10-P	10 mm	16 mm	500	100

**L-P** Cable type: flexible copper, Minimum section: 50 mm<sup>2</sup>, Maximum section: 70 mm<sup>2</sup>



Type	Øi	L	Pack qty	Min. pack qty
L14-P	11.3 mm	18 mm	500	100

**L-P** Cable type: flexible copper, Minimum section: 70 mm<sup>2</sup>, Maximum section: 95 mm<sup>2</sup>


Type	Øi	L	Pack qty	Min. pack qty
L19-P	13.5 mm	19 mm	300	50

**L-P** Cable type: flexible copper, Minimum section: 95 mm<sup>2</sup>, Maximum section: 120 mm<sup>2</sup>


Type	Øi	L	Pack qty	Min. pack qty
L24-P	15.2 mm	22 mm	200	50

**L-P** Cable type: flexible copper, Minimum section: 120 mm<sup>2</sup>, Maximum section: 150 mm<sup>2</sup>


Type	Øi	L	Pack qty	Min. pack qty
L30-P	16.7 mm	26.5 mm	100	50

**L-P** Cable type: flexible copper, Minimum section: 150 mm<sup>2</sup>, Maximum section: 185 mm<sup>2</sup>


Type	Øi	L	Pack qty	Min. pack qty
L30-P	16.7 mm	26.5 mm	100	50
L37-P	19.2 mm	26.5 mm	100	50

**L-P** Cable type: flexible copper, Minimum section: 185 mm<sup>2</sup>, Maximum section: 240 mm<sup>2</sup>


Type	Øi	L	Pack qty	Min. pack qty
L48-P	21.1 mm	34 mm	60	15



**L-P** Cable type: flexible copper, Minimum section: 240 mm<sup>2</sup>, Maximum section: 300 mm<sup>2</sup>



Type	$\varnothing$ i	L	Pack qty	Min. pack qty
L60-P	23.7 mm	43 mm	50	25