

PARALLEL CONNECTORS L-P

Made of electrolytic copper tube Cu-ETP CWO04A conform to UNI EN 1652:1999, having the same dimensions as A-M series lugs, L-P connectors are annealed and electrolytically tin plated (minimum thickness of 3µm). They feature an internal taper to ease the introduction of the conductor.



CERTIFICATES 



2011/65/EU

PARALLEL CONNECTORS L-P


Technical characteristics

Max operating temperature range

180 °C

Material

ETP Copper electrolytically tinned



PARALLEL CONNECTORS L-P


List of products

L-P Cable type: copper, Maximum section: 10 mm²



Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L2-P	4.6 mm	10.5 mm	3,000	100	4.6 mm

L-P Cable type: flexible copper, Maximum section: 10 mm²



Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L2-P	4.6 mm	10.5 mm	3,000	100	4.6 mm

L-P Cable type: copper, Maximum section: 16 mm²



Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L3-P	5.8 mm	11.5 mm	2,000	100	5.8 mm

L-P Cable type: flexible copper, Maximum section: 16 mm²



Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L3-P	5.8 mm	11.5 mm	2,000	100	5.8 mm

L-P Cable type: copper, Maximum section: 25 mm²


Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L5-P	7 mm	13 mm	1,500	100	7 mm

L-P Cable type: flexible copper, Maximum section: 25 mm²


Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L5-P	7 mm	13 mm	1,500	100	7 mm

L-P Cable type: copper, Maximum section: 35 mm²


Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L7-P	8.9 mm	14 mm	500	100	8.9 mm

L-P Cable type: copper, Maximum section: 50 mm²


Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L10-P	10 mm	16 mm	500	100	10 mm

L-P Cable type: copper, Maximum section: 70 mm²


Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L14-P	11.3 mm	18 mm	500	100	11.3 mm

L-P Cable type: copper, Maximum section: 95 mm²


Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L19-P	13.5 mm	19 mm	300	50	13.5 mm

L-P Cable type: copper, Maximum section: 120 mm²


Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L24-P	15.2 mm	22 mm	200	50	15.2 mm

L-P Cable type: copper, Maximum section: 150 mm²


Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L30-P	16.7 mm	26.5 mm	100	50	16.7 mm

L-P Cable type: copper, Maximum section: 185 mm²


Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L37-P	19.2 mm	26.5 mm	100	50	19.2 mm

L-P Cable type: copper, Maximum section: 240 mm²


Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L48-P	21.1 mm	34 mm	60	15	21.1 mm

L-P Cable type: copper, Maximum section: 300 mm²


Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L60-P	23.7 mm	43 mm	50	25	23.7 mm

L-P Cable type: flexible copper, Minimum section: 0.25 mm², Maximum section: 1.5 mm²


Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L03-P	1.8 mm	6 mm	10,000	100	1.8 mm

L-P Cable type: copper, Minimum section: 0.25 mm², Maximum section: 1.5 mm²


Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L03-P	1.8 mm	6 mm	10,000	100	1.8 mm

L-P Cable type: copper, Minimum section: 1.5 mm², Maximum section: 2.5 mm²


Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L06-P	2.4 mm	6 mm	5,000	100	2.4 mm

L-P Cable type: flexible copper, Minimum section: 1.5 mm², Maximum section: 2.5 mm²


Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L06-P	2.4 mm	6 mm	5,000	100	2.4 mm

L-P Cable type: flexible copper, Minimum section: 4 mm², Maximum section: 6 mm²



Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L1-P	3.6 mm	9 mm	5,000	100	3.6 mm

L-P Cable type: copper, Minimum section: 4 mm², Maximum section: 6 mm²



Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L1-P	3.6 mm	9 mm	5,000	100	3.6 mm

L-P Cable type: flexible copper, Minimum section: 25 mm², Maximum section: 35 mm²



Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L7-P	8.9 mm	14 mm	500	100	8.9 mm

L-P Cable type: flexible copper, Minimum section: 35 mm², Maximum section: 50 mm²



Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L10-P	10 mm	16 mm	500	100	10 mm

L-P Cable type: flexible copper, Minimum section: 50 mm², Maximum section: 70 mm²



Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L14-P	11.3 mm	18 mm	500	100	11.3 mm

L-P Cable type: flexible copper, Minimum section: 70 mm², Maximum section: 95 mm²


Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L19-P	13.5 mm	19 mm	300	50	13.5 mm

L-P Cable type: flexible copper, Minimum section: 95 mm², Maximum section: 120 mm²


Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L24-P	15.2 mm	22 mm	200	50	15.2 mm

L-P Cable type: flexible copper, Minimum section: 120 mm², Maximum section: 150 mm²


Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L30-P	16.7 mm	26.5 mm	100	50	16.7 mm

L-P Cable type: flexible copper, Minimum section: 150 mm², Maximum section: 185 mm²


Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L30-P	16.7 mm	26.5 mm	100	50	16.7 mm
L37-P	19.2 mm	26.5 mm	100	50	19.2 mm

L-P Cable type: flexible copper, Minimum section: 185 mm², Maximum section: 240 mm²


Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L48-P	21.1 mm	34 mm	60	15	21.1 mm

L-P Cable type: flexible copper, Minimum section: 240 mm², Maximum section: 300 mm²



Type	Øi	L	Pack qty	Min. pack qty	Maximum diameter of the stripped cable
L60-P	23.7 mm	43 mm	50	25	23.7 mm