

FLEXIBLE BRAIDS FL

Flexible Braids in bright copper

Flexible braids are manufactured from electrolytic copper wire. Braids of different conductor sizes or lengths are available on request. Standard finish - bright copper Flexible braids can be supplied tin plated, in this case add the suffix "ST" to reference.



CERTIFICATES 




2011/65/EU

FLEXIBLE BRAIDS FL

Technical characteristics

Material (Body)

Electrolytic copper



FLEXIBLE BRAIDS FL

List of products

FL


Type	Ø Stud mm	B	N	L	d	Pack qty
FL10-150	8 mm	17 mm	10 mm	150 mm	8.5 mm	50
FL10-200	8 mm	17 mm	10 mm	200 mm	8.5 mm	50
FL10-250	8 mm	17 mm	10 mm	250 mm	8.5 mm	50
FL16-150	8 mm	17 mm	10 mm	150 mm	8.5 mm	50
FL16-200	8 mm	17 mm	10 mm	200 mm	8.5 mm	50
FL16-250	8 mm	17 mm	10 mm	250 mm	8.5 mm	50
FL16-320	8 mm	17 mm	10 mm	320 mm	8.5 mm	50
FL16-350	8 mm	17 mm	10 mm	350 mm	8.5 mm	50
FL16-420	8 mm	17 mm	10 mm	420 mm	8.5 mm	50
FL16-570	8 mm	17 mm	10 mm	570 mm	8.5 mm	50
FL16-660	8 mm	17 mm	10 mm	660 mm	8.5 mm	50
FL25-150	8 mm	21 mm	10 mm	150 mm	8.5 mm	50
FL25-200	8 mm	21 mm	10 mm	200 mm	8.5 mm	50
FL25-250	8 mm	21 mm	10 mm	250 mm	8.5 mm	50
FL25-300	8 mm	21 mm	10 mm	300 mm	8.5 mm	50