

FLEXIBLE BRAIDS FL-ST

Flexible braids are manufactured from electrolytic copper wire. Braids of different conductor sizes or lengths are available on request. Standard finish - bright copper Flexible braids can be supplied tin plated, in this case add the suffix "ST" to reference.



CERTIFICATES 




2011/65/EU

FLEXIBLE BRAIDS FL-ST

Technical characteristics

Material (Body)

Tinned electrolytic copper electrolytically



FLEXIBLE BRAIDS FL-ST

List of products

FL-ST



Type	Ø Stud mm	Width	N	Length	Diameter of the hole	Pack qty
FL10-150ST	8 mm	17 mm	10 mm	150 mm	8.5 mm	50
FL10-200ST	8 mm	17 mm	10 mm	200 mm	8.5 mm	50
FL10-250ST	8 mm	17 mm	10 mm	250 mm	8.5 mm	50
FL16-150ST	8 mm	17 mm	10 mm	150 mm	8.5 mm	50
FL16-200ST	8 mm	17 mm	10 mm	200 mm	8.5 mm	50
FL16-250ST	8 mm	17 mm	10 mm	250 mm	8.5 mm	50
FL16-320ST	8 mm	17 mm	10 mm	320 mm	8.5 mm	50
FL16-350ST	8 mm	17 mm	10 mm	350 mm	8.5 mm	50
FL16-420ST	8 mm	17 mm	10 mm	420 mm	8.5 mm	50
FL16-570ST	8 mm	17 mm	10 mm	570 mm	8.5 mm	50
FL16-660ST	8 mm	17 mm	10 mm	660 mm	8.5 mm	50
FL25-150ST	8 mm	21 mm	10 mm	150 mm	8.5 mm	50
FL25-200ST	8 mm	21 mm	10 mm	200 mm	8.5 mm	50
FL25-250ST	8 mm	21 mm	10 mm	250 mm	8.5 mm	50
FL25-300ST	8 mm	21 mm	10 mm	300 mm	8.5 mm	50