

## UNINSULATED PIN CONNECTORS A-P

A-P series pin connectors are designed to terminate conductors into contact blocks. They are manufactured from copper strip, rolled, brazed and tin plated.

The terminals are manufactured from electrolytic Copper Cu-ETP CWO04A according to UNI EN 13599 and are tin plated to a minimum thickness of 3m.



---

CERTIFICATES 




2011/65/EU

# UNINSULATED PIN CONNECTORS **A-P**

## *Technical characteristics*

Material (Body)


ETP Copper electrolytically tinned



# UNINSULATED PIN CONNECTORS A-P


## List of products

### A-P Cable type: copper, Maximum section: 10 mm<sup>2</sup>




Type	Ø	B	P	L	Pack qty	Min. pack qty
A2-P12	4.8 mm	4.3 mm	14.5 mm	23.5 mm	1,000	100

### A-P Cable type: flexible copper, Maximum section: 10 mm<sup>2</sup>




Type	Ø	B	P	L	Pack qty	Min. pack qty
A2-P12	4.8 mm	4.3 mm	14.5 mm	23.5 mm	1,000	100

### A-P Cable type: copper, Maximum section: 16 mm<sup>2</sup>




Type	Ø	B	P	L	Pack qty	Min. pack qty
A3-P14	5.9 mm	5.5 mm	18 mm	28 mm	1,500	100


### A-P Cable type: flexible copper, Maximum section: 16 mm<sup>2</sup>




Type	Ø	B	P	L	Pack qty	Min. pack qty
A3-P14	5.9 mm	5.5 mm	18 mm	28 mm	1,500	100

**A-P** Cable type: flexible copper, Maximum section: 25 mm<sup>2</sup>



Type	Ø	B	P	L	Pack qty	Min. pack qty
A5-P16	7 mm	7 mm	20.3 mm	32 mm	1,000	100

**A-P** Cable type: copper, Maximum section: 25 mm<sup>2</sup>



Type	Ø	B	P	L	Pack qty	Min. pack qty
A5-P16	7 mm	7 mm	20.3 mm	32 mm	1,000	100

**A-P** Cable type: copper, Maximum section: 35 mm<sup>2</sup>



Type	Ø	B	P	L	Pack qty	Min. pack qty
A7-P20	8.9 mm	8 mm	24.5 mm	39 mm	500	100

**A-P** Cable type: flexible copper, Maximum section: 35 mm<sup>2</sup>



Type	Ø	B	P	L	Pack qty	Min. pack qty
A7-P20	8.9 mm	8 mm	24.5 mm	39 mm	500	100

**A-P** Cable type: copper, Maximum section: 50 mm<sup>2</sup>



Type	Ø	B	P	L	Pack qty	Min. pack qty
A10-P25	10 mm	9.5 mm	26 mm	45 mm	250	50

**A-P** Cable type: flexible copper, Maximum section: 50 mm<sup>2</sup>



Type	Ø	B	P	L	Pack qty	Min. pack qty
A10-P25	10 mm	9.5 mm	26 mm	45 mm	250	50

**A-P** Cable type: copper, Maximum section: 70 mm<sup>2</sup>



Type	Ø	B	P	L	Pack qty	Min. pack qty
A14-P30	11.5 mm	11 mm	31 mm	55 mm	200	50

**A-P** Cable type: flexible copper, Maximum section: 70 mm<sup>2</sup>


Type	Ø	B	P	L	Pack qty	Min. pack qty
A14-P30	11.5 mm	11 mm	31 mm	55 mm	200	50


**A-P** Cable type: flexible copper, Minimum section: 25 mm<sup>2</sup>, Maximum section: 35 mm<sup>2</sup>


Type	Ø	B	P	L	Pack qty	Min. pack qty
A7-P20	8.9 mm	8 mm	24.5 mm	39 mm	500	100

**A-P** Cable type: flexible copper, Minimum section: 35 mm<sup>2</sup>, Maximum section: 50 mm<sup>2</sup>


Type	Ø	B	P	L	Pack qty	Min. pack qty
A10-P25	10 mm	9.5 mm	26 mm	45 mm	250	50

**A-P** Cable type: flexible copper, Minimum section: 50 mm<sup>2</sup>, Maximum section: 70 mm<sup>2</sup>



Type	Ø	B	P	L	Pack qty	Min. pack qty
A14-P30	11.5 mm	11 mm	31 mm	55 mm	200	50