



UNINSULATED PIN CONNECTORS A-P

A-P series pin connectors are designed to terminate conductors into contact blocks. They are manufactured from copper strip, rolled, brazed and tin plated.



CERTIFICATES 


 2011/65/EU

UNINSULATED PIN CONNECTORS **A-P**

Technical characteristics

Material (Body)


ETP Copper electrolytically tinned



UNINSULATED PIN CONNECTORS A-P


List of products

A-P Cable type: copper, Maximum section: 10 mm²




| Type | Ø | B | P | L | Pack qty | Min. pack qty |
|--------|--------|--------|---------|---------|----------|---------------|
| A2-P12 | 4.8 mm | 4.3 mm | 14.5 mm | 23.5 mm | 1,000 | 100 |

A-P Cable type: flexible copper, Maximum section: 10 mm²




| Type | Ø | B | P | L | Pack qty | Min. pack qty |
|--------|--------|--------|---------|---------|----------|---------------|
| A2-P12 | 4.8 mm | 4.3 mm | 14.5 mm | 23.5 mm | 1,000 | 100 |

A-P Cable type: copper, Maximum section: 16 mm²




| Type | Ø | B | P | L | Pack qty | Min. pack qty |
|--------|--------|--------|-------|-------|----------|---------------|
| A3-P14 | 5.9 mm | 5.5 mm | 18 mm | 28 mm | 1,500 | 100 |


A-P Cable type: flexible copper, Maximum section: 16 mm²




| Type | Ø | B | P | L | Pack qty | Min. pack qty |
|--------|--------|--------|-------|-------|----------|---------------|
| A3-P14 | 5.9 mm | 5.5 mm | 18 mm | 28 mm | 1,500 | 100 |

A-P Cable type: flexible copper, Maximum section: 25 mm²



| Type | Ø | B | P | L | Pack qty | Min. pack qty |
|--------|------|------|---------|-------|----------|---------------|
| A5-P16 | 7 mm | 7 mm | 20.3 mm | 32 mm | 1,000 | 100 |

A-P Cable type: copper, Maximum section: 25 mm²



| Type | Ø | B | P | L | Pack qty | Min. pack qty |
|--------|------|------|---------|-------|----------|---------------|
| A5-P16 | 7 mm | 7 mm | 20.3 mm | 32 mm | 1,000 | 100 |

A-P Cable type: copper, Maximum section: 35 mm²



| Type | Ø | B | P | L | Pack qty | Min. pack qty |
|--------|--------|------|---------|-------|----------|---------------|
| A7-P20 | 8.9 mm | 8 mm | 24.5 mm | 39 mm | 500 | 100 |

A-P Cable type: flexible copper, Maximum section: 35 mm²



| Type | Ø | B | P | L | Pack qty | Min. pack qty |
|--------|--------|------|---------|-------|----------|---------------|
| A7-P20 | 8.9 mm | 8 mm | 24.5 mm | 39 mm | 500 | 100 |

A-P Cable type: copper, Maximum section: 50 mm²



| Type | Ø | B | P | L | Pack qty | Min. pack qty |
|---------|-------|--------|-------|-------|----------|---------------|
| A10-P25 | 10 mm | 9.5 mm | 26 mm | 45 mm | 250 | 50 |

A-P Cable type: flexible copper, Maximum section: 50 mm²



| Type | Ø | B | P | L | Pack qty | Min. pack qty |
|---------|-------|--------|-------|-------|----------|---------------|
| A10-P25 | 10 mm | 9.5 mm | 26 mm | 45 mm | 250 | 50 |

A-P Cable type: copper, Maximum section: 70 mm²



| Type | Ø | B | P | L | Pack qty | Min. pack qty |
|---------|---------|-------|-------|-------|----------|---------------|
| A14-P30 | 11.5 mm | 11 mm | 31 mm | 55 mm | 200 | 50 |

A-P Cable type: flexible copper, Maximum section: 70 mm²


| Type | Ø | B | P | L | Pack qty | Min. pack qty |
|---------|---------|-------|-------|-------|----------|---------------|
| A14-P30 | 11.5 mm | 11 mm | 31 mm | 55 mm | 200 | 50 |


A-P Cable type: flexible copper, Minimum section: 25 mm², Maximum section: 35 mm²


| Type | Ø | B | P | L | Pack qty | Min. pack qty |
|--------|--------|------|---------|-------|----------|---------------|
| A7-P20 | 8.9 mm | 8 mm | 24.5 mm | 39 mm | 500 | 100 |

A-P Cable type: flexible copper, Minimum section: 35 mm², Maximum section: 50 mm²


| Type | Ø | B | P | L | Pack qty | Min. pack qty |
|---------|-------|--------|-------|-------|----------|---------------|
| A10-P25 | 10 mm | 9.5 mm | 26 mm | 45 mm | 250 | 50 |

A-P Cable type: flexible copper, Minimum section: 50 mm², Maximum section: 70 mm²



| Type | Ø | B | P | L | Pack qty | Min. pack qty |
|---------|---------|-------|-------|-------|----------|---------------|
| A14-P30 | 11.5 mm | 11 mm | 31 mm | 55 mm | 200 | 50 |