

## CABLE CLAMPS 23

Cembre parallel cable clamps single or double bolt fixing.  
Bolts and nuts are zinc plated with a minimum thickness of 2÷4 m  
to avoid oxidation.





CERTIFICATES 

 BT 2006/95/CE  2011/65/EU

## CABLE CLAMPS 23

### *Technical characteristics*

Material (Body)	Brass CB754S
Material (Screws)	Electroplated galvanized steel
Material (Nut)	Electroplated galvanized steel



## CABLE CLAMPS 23

### List of products

**23**


Type	Bolt	Minimum section	Maximum section	Ø A min	Ø A max	B	L	Pack qty
2323	1	6 mm <sup>2</sup>	16 mm <sup>2</sup>	3 mm	5 mm	24 mm	20 mm	50
2326	1	16 mm <sup>2</sup>	50 mm <sup>2</sup>	5 mm	8 mm	30 mm	25 mm	50
2329	1	35 mm <sup>2</sup>	70 mm <sup>2</sup>	7 mm	12 mm	40 mm	30 mm	25
2333	2	6 mm <sup>2</sup>	16 mm <sup>2</sup>	3 mm	5 mm	24.5 mm	30 mm	50
2336	2	16 mm <sup>2</sup>	50 mm <sup>2</sup>	5 mm	8 mm	32 mm	40 mm	50
2339	2	35 mm <sup>2</sup>	70 mm <sup>2</sup>	7 mm	12 mm	40 mm	44 mm	25
2342	2	50 mm <sup>2</sup>	95 mm <sup>2</sup>	8 mm	14 mm	48 mm	48 mm	10
2344	2	70 mm <sup>2</sup>	150 mm <sup>2</sup>	12 mm	16 mm	51 mm	53 mm	10
2346	2	150 mm <sup>2</sup>	300 mm <sup>2</sup>	22 mm	16 mm	66 mm	66 mm	5