

HIGH VOLTAGE COPPER THROUGH CONNECTORS MT-TD

MT-TD and MT-GC series connectors are designed to join conductors in high voltage applications up to 33 kV. They are manufactured from high purity copper, annealed and tin plated. MT-GC series feature a solid stop which forms a barrier between the two conductors being joined, this prevents the migration of oils or greases, which may be present, in one cable contaminating the other cable. MT-TD connectors are unblocked and are suitable for joining cables of the same type.



CERTIFICATES 




2011/65/EU

HIGH VOLTAGE COPPER THROUGH CONNECTORS **MT-TD**

Technical characteristics

Material (Body)


ETP Copper electrolytically tinned



HIGH VOLTAGE COPPER THROUGH CONNECTORS MT-TD


List of products

MT-TD Cable type: copper round, Maximum section: 25 mm²




Type	Øi	Øi	L	Pack qty	Min. pack qty
MT25-TD	6.8 mm		60 mm	90	3

MT-TD Cable type: IEC228 (BS6360) Round, Maximum section: 25 mm²




Type	Øi	Øi	L	Pack qty	Min. pack qty
MT25-TD	6.8 mm		60 mm	90	3

MT-TD Cable type: IEC228 (BS6360) Sector, Maximum section: 25 mm²




Type	Øi	Øi	L	Pack qty	Min. pack qty
MT25-TD	6.8 mm		60 mm	90	3

MT-TD Cable type: copper round compact, Maximum section: 30 mm²



Type	Øi	Øi	L	Pack qty	Min. pack qty
MT40S-TD	8.2 mm		60 mm	90	3

MT-TD Cable type: copper round compact, Maximum section: 50 mm²


Type	Øi	Øi	L	Pack qty	Min. pack qty
MT50R-TD	8.7 mm		60 mm	90	3

MT-TD Cable type: copper sector shaped, Maximum section: 50 mm²


Type	Øi	Øi	L	Pack qty	Min. pack qty
MT50S-TD	9.5 mm		60 mm	90	3

MT-TD Cable type: copper sector shaped, Maximum section: 80 mm²



Type	Øi	Øi	L	Pack qty	Min. pack qty
MT95R-TD	12 mm		80 mm	30	3

MT-TD Cable type: copper sector shaped, Maximum section: 120 mm²



Type	Øi	Øi	L	Pack qty	Min. pack qty
MT150R-TD	15 mm		80 mm	30	3

MT-TD Cable type: copper sector shaped, Maximum section: 150 mm²



Type	Øi	Øi	L	Pack qty	Min. pack qty
MT150S-TD	16.5 mm		80 mm	30	3

MT-TD Cable type: copper round compact, Maximum section: 160 mm²


Type	Øi	Øi	L	Pack qty	Min. pack qty
MT150S-TD	16.5 mm		80 mm	30	3

MT-TD Cable type: copper sector shaped, Maximum section: 160 mm²



Type	Øi	Øi	L	Pack qty	Min. pack qty
MT200R-TD	17 mm		100 mm	30	3

MT-TD Cable type: copper round compact, Maximum section: 200 mm²



Type	Øi	Øi	L	Pack qty	Min. pack qty
MT200R-TD	17 mm		100 mm	30	3

MT-TD Cable type: copper sector shaped, Maximum section: 200 mm²


Type	Øi	Øi	L	Pack qty	Min. pack qty
MT240R-TD	19.2 mm		100 mm	30	3

MT-TD Cable type: copper round compact, Maximum section: 240 mm²


Type	Øi	Øi	L	Pack qty	Min. pack qty
MT240R-TD	19.2 mm		100 mm	30	3

MT-TD Cable type: copper sector shaped, Maximum section: 240 mm²


Type	Øi	Øi	L	Pack qty	Min. pack qty
MT315R-TD	21.5 mm		100 mm	30	3

MT-TD Cable type: copper round compact, Maximum section: 315 mm²



Type	Øi	Øi	L	Pack qty	Min. pack qty
MT315R-TD	21.5 mm		100 mm	30	3

MT-TD Cable type: copper sector shaped, Maximum section: 315 mm²



Type	Øi	Øi	L	Pack qty	Min. pack qty
MT315S-TD	23.7 mm		100 mm	30	3

MT-TD Cable type: IEC228 (BS6360) Round, Maximum section: 400 mm²



Type	Øi	Øi	L	Pack qty	Min. pack qty
MT400-TD	27 mm		120 mm	15	3

MT-TD Cable type: IEC228 (BS6360) Sector, Maximum section: 400 mm²


Type	Øi	Øi	L	Pack qty	Min. pack qty
MT400-TD	27 mm		120 mm	15	3

MT-TD Cable type: copper round, Maximum section: 400 mm²



Type	Øi	Øi	L	Pack qty	Min. pack qty
MT400-TD	27 mm		120 mm	15	3

MT-TD Cable type: copper round, Maximum section: 500 mm²



Type	Øi	Øi	L	Pack qty	Min. pack qty
MT500-TD	30.3 mm		118 mm	15	3

MT-TD Cable type: copper sector shaped, Minimum section: 30 mm², Maximum section: 40 mm²


Type	Øi	Øi	L	Pack qty	Min. pack qty
MT40S-TD	8.2 mm		60 mm	90	3


MT-TD Cable type: copper sector shaped, Minimum section: 63 mm², Maximum section: 70 mm²


Type	Øi	Øi	L	Pack qty	Min. pack qty
MT70S-TD	11 mm		70 mm	30	3

MT-TD Cable type: copper sector shaped, Minimum section: 95 mm², Maximum section: 100 mm²


Type	Øi	Øi	L	Pack qty	Min. pack qty
MT95S-TD	13.5 mm		80 mm	30	3

MT-TD Cable type: copper round compact, Minimum section: 120 mm², Maximum section: 150 mm²



Type	Øi	Øi	L	Pack qty	Min. pack qty
MT150R-TD	15 mm		80 mm	30	3

MT-TD Cable type: copper round, Minimum section: 600 mm², Maximum section: 630 mm²



Type	Øi	Øi	L	Pack qty	Min. pack qty
MT630-TD	33.4 mm		130 mm	9	3