

SINGLE POLE TERMINAL BLOCKS Z16

*indirect clamping
nominal section 16 sqmm*

3, 4, 5, 8 and 12 way, single pole terminal blocks. Ideal for use as an equipotential bonding connector for both industrial and domestic use.



CERTIFICATES 



CEI EN 60998-1



CEI 23-21



EN 60998-1



EN 60998-2-1

SINGLE POLE TERMINAL BLOCKS **Z16**

Technical characteristics

Easy entry	yes
UL94 class	V0
IP protection	20
Halogen Free	yes
Impulse voltage	450 V
Max application temperature	85 °C
Material (Body)	Polycarbonate
Material (Clamps)	Electroplated galvanized steel
Material (Connection plate)	ETP Copper electrolytically tinned



SINGLE POLE TERMINAL BLOCKS Z16

List of products

Z16 Cable type: copper, Minimum section: 1 mm², Maximum section: 1 mm²

Type	Height	Width	Length	No. hole	Pack qty	Weight	Clamp for DIN
Z16-8	36.5 mm	35.5 mm	50 mm	8	15	50 g	
Z16-8D	42 mm	35.5 mm	57 mm	8	10	56 g	yes

Z16 Cable type: flexible copper, Minimum section: 1 mm², Maximum section: 1 mm²

Type	Height	Width	Length	No. hole	Pack qty	Weight	Clamp for DIN
Z16-8	36.5 mm	35.5 mm	50 mm	8	15	50 g	
Z16-8D	42 mm	35.5 mm	57 mm	8	10	56 g	yes
Z16-12	36.5 mm	104.5 mm	32.5 mm	12	8	115 g	
Z16-12D	42 mm	104.5 mm	50 mm	12	5	125 g	yes

Z16 Cable type: flexible copper, Minimum section: 1.5 mm², Maximum section: 1.5 mm²

Type	Height	Width	Length	No. hole	Pack qty	Weight	Clamp for DIN
Z16-3	38 mm	38 mm	31.3 mm	3	20	52 g	
Z16-3D	44 mm	38 mm	50 mm	3	15	55.5 g	yes
Z16-4	37 mm	27 mm	54 mm	4	15	50 g	
Z16-4D	43 mm	27 mm	58 mm	4	10	54 g	yes
Z16-5N	38 mm	61 mm	31.5 mm	5	10	64.5 g	
Z16-5ND	44 mm	61 mm	50 mm	5	4	68 g	yes
Z16-8	36.5 mm	35.5 mm	50 mm	8	15	50 g	
Z16-8D	42 mm	35.5 mm	57 mm	8	10	56 g	yes
Z16-12	36.5 mm	104.5 mm	32.5 mm	12	8	115 g	
Z16-12D	42 mm	104.5 mm	50 mm	12	5	125 g	yes

Z16 Cable type: copper, Minimum section: 1.5 mm², Maximum section: 1.5 mm²

Type	Height	Width	Length	No. hole	Pack qty	Weight	Clamp for DIN
Z16-3	38 mm	38 mm	31.3 mm	3	20	52 g	
Z16-3D	44 mm	38 mm	50 mm	3	15	55.5 g	yes
Z16-5N	38 mm	61 mm	31.5 mm	5	10	64.5 g	
Z16-5ND	44 mm	61 mm	50 mm	5	4	68 g	yes
Z16-8	36.5 mm	35.5 mm	50 mm	8	15	50 g	
Z16-8D	42 mm	35.5 mm	57 mm	8	10	56 g	yes

Z16 Cable type: copper, Minimum section: 2.5 mm², Maximum section: 2.5 mm²

Type	Height	Width	Length	No. hole	Pack qty	Weight	Clamp for DIN
Z16-3	38 mm	38 mm	31.3 mm	3	20	52 g	
Z16-3D	44 mm	38 mm	50 mm	3	15	55.5 g	yes
Z16-5N	38 mm	61 mm	31.5 mm	5	10	64.5 g	
Z16-5ND	44 mm	61 mm	50 mm	5	4	68 g	yes
Z16-8	36.5 mm	35.5 mm	50 mm	8	15	50 g	
Z16-8D	42 mm	35.5 mm	57 mm	8	10	56 g	yes

Z16 Cable type: flexible copper, Minimum section: 2.5 mm², Maximum section: 2.5 mm²

Type	Height	Width	Length	No. hole	Pack qty	Weight	Clamp for DIN
Z16-3	38 mm	38 mm	31.3 mm	3	20	52 g	
Z16-3D	44 mm	38 mm	50 mm	3	15	55.5 g	yes
Z16-4	37 mm	27 mm	54 mm	4	15	50 g	
Z16-4D	43 mm	27 mm	58 mm	4	10	54 g	yes
Z16-5N	38 mm	61 mm	31.5 mm	5	10	64.5 g	
Z16-5ND	44 mm	61 mm	50 mm	5	4	68 g	yes
Z16-8	36.5 mm	35.5 mm	50 mm	8	15	50 g	
Z16-8D	42 mm	35.5 mm	57 mm	8	10	56 g	yes
Z16-12	36.5 mm	104.5 mm	32.5 mm	12	8	115 g	
Z16-12D	42 mm	104.5 mm	50 mm	12	5	125 g	yes

Z16 Cable type: flexible copper, Minimum section: 4 mm², Maximum section: 4 mm²

Type	Height	Width	Length	No. hole	Pack qty	Weight	Clamp for DIN
Z16-3	38 mm	38 mm	31.3 mm	3	20	52 g	
Z16-3D	44 mm	38 mm	50 mm	3	15	55.5 g	yes
Z16-4	37 mm	27 mm	54 mm	4	15	50 g	
Z16-4D	43 mm	27 mm	58 mm	4	10	54 g	yes
Z16-5N	38 mm	61 mm	31.5 mm	5	10	64.5 g	
Z16-5ND	44 mm	61 mm	50 mm	5	4	68 g	yes
Z16-8	36.5 mm	35.5 mm	50 mm	8	15	50 g	
Z16-8D	42 mm	35.5 mm	57 mm	8	10	56 g	yes
Z16-12	36.5 mm	104.5 mm	32.5 mm	12	8	115 g	
Z16-12D	42 mm	104.5 mm	50 mm	12	5	125 g	yes

Z16 Cable type: copper, Minimum section: 4 mm², Maximum section: 4 mm²

Type	Height	Width	Length	No. hole	Pack qty	Weight	Clamp for DIN
Z16-3	38 mm	38 mm	31.3 mm	3	20	52 g	
Z16-3D	44 mm	38 mm	50 mm	3	15	55.5 g	yes
Z16-5N	38 mm	61 mm	31.5 mm	5	10	64.5 g	
Z16-5ND	44 mm	61 mm	50 mm	5	4	68 g	yes
Z16-8	36.5 mm	35.5 mm	50 mm	8	15	50 g	
Z16-8D	42 mm	35.5 mm	57 mm	8	10	56 g	yes

Z16 Cable type: flexible copper, Minimum section: 6 mm², Maximum section: 6 mm²

Type	Height	Width	Length	No. hole	Pack qty	Weight	Clamp for DIN
Z16-3	38 mm	38 mm	31.3 mm	3	20	52 g	
Z16-3D	44 mm	38 mm	50 mm	3	15	55.5 g	yes
Z16-4	37 mm	27 mm	54 mm	4	15	50 g	
Z16-4D	43 mm	27 mm	58 mm	4	10	54 g	yes
Z16-5N	38 mm	61 mm	31.5 mm	5	10	64.5 g	
Z16-5ND	44 mm	61 mm	50 mm	5	4	68 g	yes
Z16-8	36.5 mm	35.5 mm	50 mm	8	15	50 g	
Z16-8D	42 mm	35.5 mm	57 mm	8	10	56 g	yes
Z16-12	36.5 mm	104.5 mm	32.5 mm	12	8	115 g	
Z16-12D	42 mm	104.5 mm	50 mm	12	5	125 g	yes

Z16 Cable type: copper, Minimum section: 6 mm², Maximum section: 6 mm²

Type	Height	Width	Length	No. hole	Pack qty	Weight	Clamp for DIN
Z16-3	38 mm	38 mm	31.3 mm	3	20	52 g	
Z16-3D	44 mm	38 mm	50 mm	3	15	55.5 g	yes
Z16-5N	38 mm	61 mm	31.5 mm	5	10	64.5 g	
Z16-5ND	44 mm	61 mm	50 mm	5	4	68 g	yes
Z16-8	36.5 mm	35.5 mm	50 mm	8	15	50 g	
Z16-8D	42 mm	35.5 mm	57 mm	8	10	56 g	yes

Z16 Cable type: copper, Minimum section: 10 mm², Maximum section: 10 mm²

Type	Height	Width	Length	No. hole	Pack qty	Weight	Clamp for DIN
Z16-3	38 mm	38 mm	31.3 mm	3	20	52 g	
Z16-3D	44 mm	38 mm	50 mm	3	15	55.5 g	yes
Z16-5ND	44 mm	61 mm	50 mm	5	4	68 g	yes
Z16-8	36.5 mm	35.5 mm	50 mm	8	15	50 g	
Z16-8D	42 mm	35.5 mm	57 mm	8	10	56 g	yes

Z16 Cable type: flexible copper, Minimum section: 10 mm², Maximum section: 10 mm²

Type	Height	Width	Length	No. hole	Pack qty	Weight	Clamp for DIN
Z16-3	38 mm	38 mm	31.3 mm	3	20	52 g	
Z16-3D	44 mm	38 mm	50 mm	3	15	55.5 g	yes
Z16-4	37 mm	27 mm	54 mm	4	15	50 g	
Z16-4D	43 mm	27 mm	58 mm	4	10	54 g	yes
Z16-5N	38 mm	61 mm	31.5 mm	5	10	64.5 g	
Z16-5ND	44 mm	61 mm	50 mm	5	4	68 g	yes
Z16-8	36.5 mm	35.5 mm	50 mm	8	15	50 g	
Z16-8D	42 mm	35.5 mm	57 mm	8	10	56 g	yes
Z16-12	36.5 mm	104.5 mm	32.5 mm	12	8	115 g	
Z16-12D	42 mm	104.5 mm	50 mm	12	5	125 g	yes

Z16 Cable type: copper, Minimum section: 16 mm², Maximum section: 16 mm²

Type	Height	Width	Length	No. hole	Pack qty	Weight	Clamp for DIN
Z16-3	38 mm	38 mm	31.3 mm	3	20	52 g	
Z16-3D	44 mm	38 mm	50 mm	3	15	55.5 g	yes
Z16-5N	38 mm	61 mm	31.5 mm	5	10	64.5 g	
Z16-5ND	44 mm	61 mm	50 mm	5	4	68 g	yes
Z16-8	36.5 mm	35.5 mm	50 mm	8	15	50 g	
Z16-8D	42 mm	35.5 mm	57 mm	8	10	56 g	yes

Z16 Cable type: flexible copper, Minimum section: 16 mm², Maximum section: 16 mm²

Type	Height	Width	Length	No. hole	Pack qty	Weight	Clamp for DIN
Z16-3	38 mm	38 mm	31.3 mm	3	20	52 g	
Z16-3D	44 mm	38 mm	50 mm	3	15	55.5 g	yes
Z16-4	37 mm	27 mm	54 mm	4	15	50 g	
Z16-4D	43 mm	27 mm	58 mm	4	10	54 g	yes
Z16-5N	38 mm	61 mm	31.5 mm	5	10	64.5 g	
Z16-5ND	44 mm	61 mm	50 mm	5	4	68 g	yes
Z16-8	36.5 mm	35.5 mm	50 mm	8	15	50 g	
Z16-8D	42 mm	35.5 mm	57 mm	8	10	56 g	yes
Z16-12	36.5 mm	104.5 mm	32.5 mm	12	8	115 g	
Z16-12D	42 mm	104.5 mm	50 mm	12	5	125 g	yes