

PIERCING HEADS RHT

SPECIAL TOOLS

general features

Hydraulic head complete with automatic quick coupler, for piercing holes of various diameters in copper, aluminium and steel bars with max. thickness of 10 mm. This compact and handy tool is widely used for transformer room connections, control switch boards and power plants. For operation the head must be joined to a hydraulic pump developing a pressure of 700 bar.



Available accessories (to be ordered separately):

Piercing Ø mm	6,5	8,5	9	10,5	11	13	13,5	14	15	17	19	21
Set die - indentor	RT 6,5	RT 8,5	RT 9	RT 10,5	RT 11	RT 13	RT 13,5	RT 14	RT 15	RT 17	RT 19	RT 21

max. thickness

Hole diameter (mm)	6,5	8,5	9	10,5	11	13	13,5	14	15	17	19	21
Max thickness strep in copper	10	10	10	10	10	10	10	10	10	10	8	8
Max thickness strep in steel	10	10	10	10	10	9	9	9	8	7	6	4
Punch die/set	RT 6,5	RT 8,5	RT 9	RT 10,5	RT 11	RT 13	RT 13,5	RT 14	RT 15	RT 17	RT 19	RT 21

PIERCING HEADS RHT



PIERCING HEADS RHT

List of products

RHT					
Type	Width	Length	Weight	Nominal pressure	Type of action
RHT160	153 mm	240 mm	6.5 kg	700 bar	Hole punching
RHT160-60N	181 mm	240 mm	9.2 kg	700 bar	Hole punching