

# COLOR CODED SPLICES BSCL

## *long barrel*

BSCL range of connectors are manufactured from electrolytic copper tube Cu-OF CW008A conform to UNI EN 13600. Made of electrolytic copper tube having the same dimension as C and CL series lugs, BSCL connectors are annealed and electrolytically tin plated.

They feature an internal taper at both ends to ease the introduction of the conductor and a central stop to ensure correct positioning. UL listed for US and Canada per UL486A up to 35 KV.



CERTIFICATES 



USL-CNL E125401 Canada & United States  
File no. E125401




2011/65/EU

# COLOR CODED SPLICES BSCL

## *Technical characteristics*

Material (Body)


ETP Copper electrolytically tinned



## COLOR CODED SPLICES BSCL

### List of products

#### BSCL



Type	Colour	Øi	L	Pack qty	Min. pack qty
BSCL8	Red	4.6 mm	50.5 mm	600	150
BSCL6	Blue	5.8 mm	50.5 mm	400	100
BSCL4	Grey	6.2 mm	660.5 mm	200	100
BSCL3	White	7 mm	60.5 mm	200	50
BSCL2	Brown	7.6 mm	60.5 mm	200	50
BSCL1	Green	8.9 mm	65.5 mm	200	50
BSCL1/0	Pink	10 mm	73 mm	200	50
BSCL2/0	Black	11.3 mm	79 mm	100	50
BSCL3/0	Orange	12.4 mm	79 mm	80	40
BSCL4/0	Purple	13.5 mm	85.5 mm	50	25
BSCL250	Yellow	15.2 mm	85.5 mm	50	25
BSCL300	White	16.7 mm	104.5 mm	40	20
BSCL350	Red	17.6 mm	104.5 mm	40	20
BSCL400	Blue	19.2 mm	111 mm	20	10
BSCL500	Brown	21.1 mm	117 mm	20	10
BSCL600	Green	23.7 mm	139.5 mm	20	10
BSCL750	Black	26 mm	149 mm	10	10