



MAXIBLOCK CABLE GLANDS 1900 M

Standard, metric thread M 1,5 pitch

Cable glands and accessories for control panels and engineering applications.



CERTIFICATES 

 UL 514B  UL 514B

MAXIBLOCK CABLE GLANDS 1900 M

Technical characteristics

IP protection	IP68
UL94 class	V2
Max operating temperature range (surge)	120 °C
Min operating temperature range (surge)	-20 °C
Max operating temperature range	90 °C
Min operating temperature range	-20 °C
Material (Body)	Polyamide PA6.6
Material (Sealing ring)	Neoprene®



MAXIBLOCK CABLE GLANDS 1900 M

List of products

1900 M										
Type	P	Fixing hole diameter	ØA Min	ØA Max	B	C	L Min	L Max	Colour	Pack qty
1900.M12	M12X1,5	12.2 mm	3.5 mm	7 mm	15 mm	8 mm	18 mm	22 mm	Grey RAL 7035	100
1900.M16	M16X1,5	16.2 mm	5 mm	10 mm	19 mm	8 mm	22 mm	27 mm	Grey RAL 7035	100
1900.M20	M20X1,5	20.5 mm	7 mm	13 mm	25 mm	9 mm	24 mm	30 mm	Grey RAL 7035	100
1900.M25	M25X1,5	25.4 mm	10 mm	17 mm	30 mm	10 mm	28 mm	39 mm	Grey RAL 7035	50
1900.M32	M32X1,5	32.5 mm	13 mm	21 mm	36 mm	10 mm	33 mm	44 mm	Grey RAL 7035	25
1900.M40	M40X1,5	40.5 mm	19 mm	28 mm	46 mm	10 mm	36 mm	45 mm	Grey RAL 7035	15
1900.M50	M50X1,5	50.5 mm	27 mm	35 mm	55 mm	12 mm	43 mm	52 mm	Grey RAL 7035	10
1900.M63	M63X1,5	64 mm	34 mm	45 mm	66 mm	12 mm	45 mm	55 mm	Grey RAL 7035	5
1900.M12N	M12X1,5	12.2 mm	3.5 mm	7 mm	15 mm	8 mm	18 mm	22 mm	Black RAL 9005	100
1900.M16N	M16X1,5	16.2 mm	5 mm	10 mm	19 mm	8 mm	22 mm	27 mm	Black RAL 9005	100
1900.M20N	M20X1,5	20.5 mm	7 mm	13 mm	25 mm	9 mm	24 mm	30 mm	Black RAL 9005	100
1900.M25N	M25X1,5	25.4 mm	10 mm	17 mm	30 mm	10 mm	28 mm	39 mm	Black RAL 9005	50
1900.M32N	M32X1,5	32.5 mm	13 mm	21 mm	36 mm	10 mm	33 mm	44 mm	Black RAL 9005	25
1900.M40N	M40X1,5	40.5 mm	19 mm	28 mm	46 mm	10 mm	36 mm	45 mm	Black RAL 9005	15
1900.M50N	M50X1,5	50.5 mm	27 mm	35 mm	55 mm	12 mm	43 mm	52 mm	Black RAL 9005	10
1900.M63N	M63X1,5	64 mm	34 mm	45 mm	66 mm	12 mm	45 mm	55 mm	Black RAL 9005	5
1900.M12G	M12X1,5	12.2 mm	3.5 mm	7 mm	15 mm	8 mm	18 mm	22 mm	Dark Grey RAL 7001	100
1900.M16G	M16X1,5	16.2 mm	5 mm	10 mm	19 mm	8 mm	22 mm	27 mm	Dark Grey RAL 7001	100

1900.M20G	M20X1,5	20.5 mm	7 mm	13 mm	25 mm	9 mm	24 mm	30 mm	Dark Grey RAL 7001	100
1900.M25G	M25X1,5	25.4 mm	10 mm	17 mm	30 mm	10 mm	28 mm	39 mm	Dark Grey RAL 7001	50
1900.M32G	M32X1,5	32.5 mm	13 mm	21 mm	36 mm	10 mm	33 mm	44 mm	Dark Grey RAL 7001	25
1900.M40G	M40X1,5	40.5 mm	19 mm	28 mm	46 mm	10 mm	36 mm	45 mm	Dark Grey RAL 7001	15
1900.M50G	M50X1,5	50.5 mm	27 mm	35 mm	55 mm	12 mm	43 mm	52 mm	Dark Grey RAL 7001	10
1900.M63G	M63X1,5	64 mm	34 mm	45 mm	66 mm	12 mm	45 mm	55 mm	Dark Grey RAL 7001	5