

## MAXIBLOCK CABLE GLANDS 1910 M

*Reduced cable entry, metric thread M 1,5 pitch*

Cable glands and accessories for control panels and engineering applications.



CERTIFICATES 

 UL 514B  UL 514B

# MAXIBLOCK CABLE GLANDS 1910 M

## *Technical characteristics*

IP protection	IP68
UL94 class	V2
Max operating temperature range (surge)	120 °C
Min operating temperature range (surge)	-20 °C
Max operating temperature range	90 °C
Min operating temperature range	-20 °C
Material (Body)	Polyamide PA6.6
Material (Sealing ring)	Neoprene®



# MAXIBLOCK CABLE GLANDS 1910 M

## List of products

1910 M										
Type	P	Fixing hole diameter	ØA Min	ØA Max	B	C	L Min	L Max	Colour	Pack qty
1910.M12	M12X1,5	12.2 mm	2 mm	5 mm	15 mm	8 mm	18 mm	22 mm	Grey RAL 7035	100
1910.M16	M16X1,5	16.2 mm	3 mm	7 mm	19 mm	8 mm	22 mm	27 mm	Grey RAL 7035	100
1910.M20	M20X1,5	20.5 mm	5 mm	10 mm	25 mm	9 mm	14 mm	30 mm	Grey RAL 7035	50
1910.M25	M25X1,5	25.4 mm	7 mm	13 mm	30 mm	10 mm	30 mm	41 mm	Grey RAL 7035	50
1910.M32	M32X1,5	32.5 mm	8 mm	14 mm	36 mm	10 mm	33 mm	44 mm	Grey RAL 7035	25
1910.M40	M40X1,5	40.5 mm	15 mm	23 mm	46 mm	10 mm	36 mm	45 mm	Grey RAL 7035	15
1910.M50	M50X1,5	50.5 mm	21 mm	29 mm	55 mm	12 mm	43 mm	52 mm	Grey RAL 7035	10
1910.M63	M63X1,5	64 mm	27 mm	39 mm	66 mm	12 mm	45 mm	55 mm	Grey RAL 7035	5
1910.M12N	M12X1,5	12.2 mm	2 mm	5 mm	15 mm	8 mm	18 mm	22 mm	Black RAL 9005	100
1910.M16N	M16X1,5	16.2 mm	3 mm	7 mm	19 mm	8 mm	22 mm	27 mm	Black RAL 9005	100
1910.M20N	M20X1,5	20.5 mm	5 mm	10 mm	25 mm	9 mm	14 mm	30 mm	Black RAL 9005	50
1910.M25N	M25X1,5	25.4 mm	7 mm	13 mm	30 mm	10 mm	30 mm	41 mm	Black RAL 9005	50
1910.M32N	M32X1,5	32.5 mm	8 mm	14 mm	36 mm	10 mm	33 mm	44 mm	Black RAL 9005	25
1910.M40N	M40X1,5	40.5 mm	15 mm	23 mm	46 mm	10 mm	36 mm	45 mm	Black RAL 9005	15
1910.M50N	M50X1,5	50.5 mm	21 mm	29 mm	55 mm	12 mm	43 mm	52 mm	Black RAL 9005	10
1910.M63N	M63X1,5	64 mm	27 mm	39 mm	66 mm	12 mm	45 mm	55 mm	Black RAL 9005	5
1910.M12G	M12X1,5	12.2 mm	2 mm	5 mm	15 mm	8 mm	18 mm	22 mm	Dark Grey RAL 7001	100
1910.M16G	M16X1,5	16.2 mm	3 mm	7 mm	19 mm	8 mm	22 mm	27 mm	Dark Grey RAL 7001	100

1910.M20G	M20X1,5	20.5 mm	5 mm	10 mm	25 mm	9 mm	14 mm	30 mm	Dark Grey RAL 7001	50
1910.M25G	M25X1,5	25.4 mm	7 mm	13 mm	30 mm	10 mm	30 mm	41 mm	Dark Grey RAL 7001	50
1910.M32G	M32X1,5	32.5 mm	8 mm	14 mm	36 mm	10 mm	33 mm	44 mm	Dark Grey RAL 7001	25
1910.M40G	M40X1,5	40.5 mm	15 mm	23 mm	46 mm	10 mm	36 mm	45 mm	Dark Grey RAL 7001	15
1910.M50G	M50X1,5	50.5 mm	21 mm	29 mm	55 mm	12 mm	43 mm	52 mm	Dark Grey RAL 7001	10
1910.M63G	M63X1,5	64 mm	27 mm	39 mm	66 mm	12 mm	45 mm	55 mm	Dark Grey RAL 7001	5