

MAXIBLOCK CABLE GLANDS 1901 M

Extended thread, metric thread M 1,5 pitch

Cable glands and accessories for control panels and engineering applications.



CERTIFICATES 

 UL 514B  UL 514B

MAXIBLOCK CABLE GLANDS 1901 M

Technical characteristics

| | |
|---|-----------------|
| IP protection | IP68 |
| UL94 class | V2 |
| Max operating temperature range (surge) | 120 °C |
| Min operating temperature range (surge) | -20 °C |
| Max operating temperature range | 90 °C |
| Min operating temperature range | -20 °C |
| Material (Body) | Polyamide PA6.6 |
| Material (Sealing ring) | Neoprene® |



MAXIBLOCK CABLE GLANDS 1901 M

List of products

| 1901 M | | | | | | | | | | |
|-----------|---------|----------------------|--------|--------|-------|-------|-------|-------|--------------------|----------|
| Type | P | Fixing hole diameter | ØA Min | ØA Max | B | C | L Min | L Max | Colour | Pack qty |
| 1901.M12 | M12X1,5 | 12.2 mm | 3.5 mm | 7 mm | 15 mm | 15 mm | 18 mm | 22 mm | Grey RAL 7035 | 100 |
| 1901.M16 | M16X1,5 | 16.2 mm | 5 mm | 10 mm | 19 mm | 15 mm | 22 mm | 27 mm | Grey RAL 7035 | 100 |
| 1901.M20 | M20X1,5 | 20.5 mm | 7 mm | 13 mm | 25 mm | 15 mm | 24 mm | 30 mm | Grey RAL 7035 | 50 |
| 1901.M25 | M25X1,5 | 25.4 mm | 10 mm | 17 mm | 30 mm | 15 mm | 30 mm | 41 mm | Grey RAL 7035 | 50 |
| 1901.M32 | M32X1,5 | 32.5 mm | 13 mm | 21 mm | 36 mm | 15 mm | 33 mm | 44 mm | Grey RAL 7035 | 25 |
| 1901.M40 | M40X1,5 | 40.5 mm | 19 mm | 28 mm | 46 mm | 18 mm | 36 mm | 45 mm | Grey RAL 7035 | 15 |
| 1901.M50 | M50X1,5 | 50.5 mm | 27 mm | 35 mm | 55 mm | 18 mm | 43 mm | 52 mm | Grey RAL 7035 | 10 |
| 1901.M63 | M63X1,5 | 64 mm | 34 mm | 45 mm | 66 mm | 18 mm | 45 mm | 55 mm | Grey RAL 7035 | 5 |
| 1901.M12N | M12X1,5 | 12.2 mm | 3.5 mm | 7 mm | 15 mm | 15 mm | 18 mm | 22 mm | Black RAL 9005 | 100 |
| 1901.M16N | M16X1,5 | 16.2 mm | 5 mm | 10 mm | 19 mm | 15 mm | 22 mm | 27 mm | Black RAL 9005 | 100 |
| 1901.M20N | M20X1,5 | 20.5 mm | 7 mm | 13 mm | 25 mm | 15 mm | 24 mm | 30 mm | Black RAL 9005 | 50 |
| 1901.M25N | M25X1,5 | 25.4 mm | 10 mm | 17 mm | 30 mm | 15 mm | 30 mm | 41 mm | Black RAL 9005 | 50 |
| 1901.M32N | M32X1,5 | 32.5 mm | 13 mm | 21 mm | 36 mm | 15 mm | 33 mm | 44 mm | Black RAL 9005 | 25 |
| 1901.M40N | M40X1,5 | 40.5 mm | 19 mm | 28 mm | 46 mm | 18 mm | 36 mm | 45 mm | Black RAL 9005 | 15 |
| 1901.M50N | M50X1,5 | 50.5 mm | 27 mm | 35 mm | 55 mm | 18 mm | 43 mm | 52 mm | Black RAL 9005 | 10 |
| 1901.M63N | M63X1,5 | 64 mm | 34 mm | 45 mm | 66 mm | 18 mm | 45 mm | 55 mm | Black RAL 9005 | 5 |
| 1901.M12G | M12X1,5 | 12.2 mm | 3.5 mm | 7 mm | 15 mm | 15 mm | 18 mm | 22 mm | Dark Grey RAL 7001 | 100 |
| 1901.M16G | M16X1,5 | 16.2 mm | 5 mm | 10 mm | 19 mm | 15 mm | 22 mm | 27 mm | Dark Grey RAL 7001 | 100 |

| | | | | | | | | | | |
|-----------|---------|---------|-------|-------|-------|-------|-------|-------|--------------------|----|
| 1901.M20G | M20X1,5 | 20.5 mm | 7 mm | 13 mm | 25 mm | 15 mm | 24 mm | 30 mm | Dark Grey RAL 7001 | 50 |
| 1901.M25G | M25X1,5 | 25.4 mm | 10 mm | 17 mm | 30 mm | 15 mm | 30 mm | 41 mm | Dark Grey RAL 7001 | 50 |
| 1901.M32G | M32X1,5 | 32.5 mm | 13 mm | 21 mm | 36 mm | 15 mm | 33 mm | 44 mm | Dark Grey RAL 7001 | 25 |
| 1901.M40G | M40X1,5 | 40.5 mm | 19 mm | 28 mm | 46 mm | 18 mm | 36 mm | 45 mm | Dark Grey RAL 7001 | 15 |
| 1901.M50G | M50X1,5 | 50.5 mm | 27 mm | 35 mm | 55 mm | 18 mm | 43 mm | 52 mm | Dark Grey RAL 7001 | 10 |
| 1901.M63G | M63X1,5 | 64 mm | 34 mm | 45 mm | 66 mm | 18 mm | 45 mm | 55 mm | Dark Grey RAL 7001 | 5 |