



MAXIBLOCK CABLE GLANDS 1900 PG

Standard, Pg thread

Cable glands and accessories for control panels and engineering applications.



CERTIFICATES 

 UL 514B  UL 514B

MAXIBLOCK CABLE GLANDS 1900 PG

Technical characteristics

IP protection	IP68
UL94 class	V2
Max operating temperature range (surge)	120 °C
Min operating temperature range (surge)	-20 °C
Max operating temperature range	90 °C
Min operating temperature range	-20 °C
Material (Body)	Polyamide PA6.6
Material (Sealing ring)	Neoprene®



MAXIBLOCK CABLE GLANDS 1900 PG

List of products

1900 Pg										
Type	P	Fixing hole diameter	ØA Min	ØA Max	B	C	L Min	L Max	Colour	Pack qty
1900DP.09	Pg9	15.5 mm	5 mm	8 mm	19 mm	8 mm	22 mm	26 mm	Grey RAL 7035	100
1900.07	Pg7	12.7 mm	3.5 mm	7 mm	15 mm	8 mm	18 mm	22 mm	Grey RAL 7035	100
1900.09	Pg9	15.5 mm	5 mm	8 mm	19 mm	8 mm	22 mm	26 mm	Grey RAL 7035	100
1900.11	Pg11	18.8 mm	5 mm	10 mm	22 mm	8 mm	23 mm	28 mm	Grey RAL 7035	100
1900.13	Pg13,5	20.5 mm	7 mm	12 mm	24 mm	9 mm	24 mm	29 mm	Grey RAL 7035	100
1900.16	Pg16	22.6 mm	10 mm	14 mm	27 mm	10 mm	26 mm	31 mm	Grey RAL 7035	50
1900.21	Pg21	28.5 mm	13 mm	18 mm	33 mm	12 mm	30 mm	35 mm	Grey RAL 7035	50
1900.29	Pg29	37.2 mm	18 mm	25 mm	42 mm	12 mm	33 mm	39 mm	Grey RAL 7035	25
1900.36	Pg36	47.2 mm	20 mm	32 mm	53 mm	14 mm	42 mm	49 mm	Grey RAL 7035	10
1900.42	Pg42	54.2 mm	28 mm	38 mm	60 mm	14 mm	42 mm	50 mm	Grey RAL 7035	5
1900.48	Pg48	60 mm	37 mm	45 mm	66 mm	15 mm	45 mm	55 mm	Grey RAL 7035	5
1900.07N	Pg7	12.7 mm	3.5 mm	7 mm	15 mm	8 mm	18 mm	22 mm	Black RAL 9005	100
1900.09N	Pg9	15.5 mm	5 mm	8 mm	19 mm	8 mm	22 mm	26 mm	Black RAL 9005	100
1900.11N	Pg11	18.8 mm	5 mm	10 mm	22 mm	8 mm	23 mm	28 mm	Black RAL 9005	100
1900.13N	Pg13,5	20.5 mm	7 mm	12 mm	24 mm	9 mm	24 mm	29 mm	Black RAL 9005	100
1900.16N	Pg16	22.6 mm	10 mm	14 mm	27 mm	10 mm	26 mm	31 mm	Black RAL 9005	50
1900.21N	Pg21	28.5 mm	13 mm	18 mm	33 mm	12 mm	30 mm	35 mm	Black RAL 9005	50
1900.29N	Pg29	37.2 mm	18 mm	25 mm	42 mm	12 mm	33 mm	39 mm	Black RAL 9005	25

1900.36N	Pg36	47.2 mm	20 mm	32 mm	53 mm	14 mm	42 mm	49 mm	Black RAL 9005	10
1900.42N	Pg42	54.2 mm	28 mm	38 mm	60 mm	14 mm	42 mm	50 mm	Black RAL 9005	5
1900.48N	Pg48	60 mm	37 mm	45 mm	66 mm	15 mm	45 mm	55 mm	Black RAL 9005	5
1900.07G	Pg7	12.7 mm	3.5 mm	7 mm	15 mm	8 mm	18 mm	22 mm	Dark Grey RAL 7001	100
1900.09G	Pg9	15.5 mm	5 mm	8 mm	19 mm	8 mm	22 mm	26 mm	Dark Grey RAL 7001	100
1900.11G	Pg11	18.8 mm	5 mm	10 mm	22 mm	8 mm	23 mm	28 mm	Dark Grey RAL 7001	100
1900.13G	Pg13,5	20.5 mm	7 mm	12 mm	24 mm	9 mm	24 mm	29 mm	Dark Grey RAL 7001	100
1900.16G	Pg16	22.6 mm	10 mm	14 mm	27 mm	10 mm	26 mm	31 mm	Dark Grey RAL 7001	50
1900.21G	Pg21	28.5 mm	13 mm	18 mm	33 mm	12 mm	30 mm	35 mm	Dark Grey RAL 7001	50
1900.29G	Pg29	37.2 mm	18 mm	25 mm	42 mm	12 mm	33 mm	39 mm	Dark Grey RAL 7001	25
1900.36G	Pg36	47.2 mm	20 mm	32 mm	53 mm	14 mm	42 mm	49 mm	Dark Grey RAL 7001	10
1900.42G	Pg42	54.2 mm	28 mm	38 mm	60 mm	14 mm	42 mm	50 mm	Dark Grey RAL 7001	5
1900.48G	Pg48	60 mm	37 mm	45 mm	66 mm	15 mm	45 mm	55 mm	Dark Grey RAL 7001	5