

MAXIBLOCK CABLE GLANDS 1910 PG

Reduced cable entry, Pg thread

Cable glands and accessories for control panels and engineering applications.



MAXIBLOCK CABLE GLANDS 1910 PG

Technical characteristics

IP protection	IP68
UL94 class	V2
Max operating temperature range (surge)	120 °C
Min operating temperature range (surge)	-20 °C
Max operating temperature range	90 °C
Min operating temperature range	-20 °C
Material (Body)	Polyamide PA6.6
Material (Sealing ring)	Neoprene®



MAXIBLOCK CABLE GLANDS 1910 PG

List of products

1910 Pg										
Type	P	Fixing hole diameter	ØA Min	ØA Max	B	C	L Min	L Max	Colour	Pack qty
1910.07	Pg7	12.7 mm	2 mm	5 mm	15 mm	8 mm	18 mm	22 mm	Grey RAL 7035	100
1910.09	Pg9	15.5 mm	2 mm	6 mm	19 mm	8 mm	22 mm	26 mm	Grey RAL 7035	100
1910.11	Pg11	18.8 mm	4 mm	7 mm	22 mm	8 mm	23 mm	28 mm	Grey RAL 7035	100
1910.13	Pg13,5	20.5 mm	5 mm	10 mm	24 mm	9 mm	24 mm	29 mm	Grey RAL 7035	100
1910.16	Pg16	22.6 mm	6 mm	12 mm	27 mm	10 mm	26 mm	31 mm	Grey RAL 7035	50
1910.21	Pg21	28.5 mm	9 mm	15 mm	33 mm	12 mm	30 mm	35 mm	Grey RAL 7035	50
1910.29	Pg29	37.2 mm	12 mm	20 mm	42 mm	12 mm	33 mm	39 mm	Grey RAL 7035	25
1910.36	Pg36	47.2 mm	18 mm	26 mm	53 mm	14 mm	42 mm	49 mm	Grey RAL 7035	10
1910.42	Pg42	54.2 mm	25 mm	31 mm	60 mm	14 mm	42 mm	50 mm	Grey RAL 7035	5
1910.48	Pg48	60 mm	27 mm	39 mm	66 mm	15 mm	45 mm	55 mm	Grey RAL 7035	5
1910.07N	Pg7	12.7 mm	2 mm	5 mm	15 mm	8 mm	18 mm	22 mm	Black RAL 9005	100
1910.09N	Pg9	15.5 mm	2 mm	6 mm	19 mm	8 mm	22 mm	26 mm	Black RAL 9005	100
1910.11N	Pg11	18.8 mm	4 mm	7 mm	22 mm	8 mm	23 mm	28 mm	Black RAL 9005	100
1910.13N	Pg13,5	20.5 mm	5 mm	10 mm	24 mm	9 mm	24 mm	29 mm	Black RAL 9005	100
1910.16N	Pg16	22.6 mm	6 mm	12 mm	27 mm	10 mm	26 mm	31 mm	Black RAL 9005	50
1910.21N	Pg21	28.5 mm	9 mm	15 mm	33 mm	12 mm	30 mm	35 mm	Black RAL 9005	50
1910.29N	Pg29	37.2 mm	12 mm	20 mm	42 mm	12 mm	33 mm	39 mm	Black RAL 9005	25
1910.36N	Pg36	47.2 mm	18 mm	26 mm	53 mm	14 mm	42 mm	49 mm	Black RAL 9005	10
1910.42N	Pg42	54.2 mm	25 mm	31 mm	60 mm	14 mm	42 mm	50 mm	Black RAL 9005	5
1910.48N	Pg48	60 mm	27 mm	39 mm	66 mm	15 mm	45 mm	55 mm	Black RAL 9005	5