



# MAXIBLOCK CABLE GLANDS 1901 PG

*Extended thread, Pg thread*

Cable glands and accessories for control panels and engineering applications.



CERTIFICATES 

 UL 514B  UL 514B

# MAXIBLOCK CABLE GLANDS 1901 PG

## *Technical characteristics*

IP protection	IP68
UL94 class	V2
Max operating temperature range (surge)	120 °C
Min operating temperature range (surge)	-20 °C
Max operating temperature range	90 °C
Min operating temperature range	-20 °C
Material (Body)	Polyamide PA6.6
Material (Sealing ring)	Neoprene®



# MAXIBLOCK CABLE GLANDS 1901 PG

*List of products*

## 1901 Pg

Type	P	Fixing hole diameter	ØA Min	ØA Max	B	C	L Min	L Max	Colour	Pack qty
1901.07	Pg7	12.7 mm	3.5 mm	7 mm	15 mm	15 mm	18 mm	22 mm	Grey RAL 7035	100
1901.09	Pg9	15.5 mm	5 mm	8 mm	19 mm	15 mm	22 mm	26 mm	Grey RAL 7035	100
1901.11	Pg11	18.8 mm	5 mm	10 mm	22 mm	15 mm	23 mm	28 mm	Grey RAL 7035	100
1901.13	Pg13,5	20.5 mm	7 mm	12 mm	24 mm	15 mm	24 mm	29 mm	Grey RAL 7035	100
1901.16	Pg16	22.6 mm	10 mm	14 mm	27 mm	15 mm	26 mm	31 mm	Grey RAL 7035	50
1901.21	Pg21	28.5 mm	13 mm	18 mm	33 mm	15 mm	30 mm	35 mm	Grey RAL 7035	50
1901.29	Pg29	37.2 mm	18 mm	25 mm	42 mm	15 mm	33 mm	39 mm	Grey RAL 7035	25
1901.36	Pg36	47.2 mm	20 mm	32 mm	53 mm	18 mm	42 mm	49 mm	Grey RAL 7035	10
1901.42	Pg42	54.2 mm	28 mm	38 mm	60 mm	18 mm	42 mm	50 mm	Grey RAL 7035	5
1901.48	Pg48	60 mm	37 mm	45 mm	66 mm	18 mm	45 mm	55 mm	Grey RAL 7035	5
1901.07N	Pg7	12.7 mm	3.5 mm	7 mm	15 mm	15 mm	18 mm	22 mm	Black RAL 9005	100
1901.09N	Pg9	15.5 mm	5 mm	8 mm	19 mm	15 mm	22 mm	26 mm	Black RAL 9005	100
1901.11N	Pg11	18.8 mm	5 mm	10 mm	22 mm	15 mm	23 mm	28 mm	Black RAL 9005	100
1901.13N	Pg13,5	20.5 mm	7 mm	12 mm	24 mm	15 mm	24 mm	29 mm	Black RAL 9005	100
1901.16N	Pg16	22.6 mm	10 mm	14 mm	27 mm	15 mm	26 mm	31 mm	Black RAL 9005	50
1901.21N	Pg21	28.5 mm	13 mm	18 mm	33 mm	15 mm	30 mm	35 mm	Black RAL 9005	50
1901.29N	Pg29	37.2 mm	18 mm	25 mm	42 mm	15 mm	33 mm	39 mm	Black RAL 9005	25
1901.36N	Pg36	47.2 mm	20 mm	32 mm	53 mm	18 mm	42 mm	49 mm	Black RAL 9005	10
1901.42N	Pg42	54.2 mm	28 mm	38 mm	60 mm	18 mm	42 mm	50 mm	Black RAL 9005	5
1901.48N	Pg48	60 mm	37 mm	45 mm	66 mm	18 mm	45 mm	55 mm	Black RAL 9005	5