

MAXIBLOCK CABLE GLANDS 1900/X M

Standard factory fitted with locknuts with collar, metric thread M 1,5 pitch

Cable glands and accessories for control panels and engineering applications.



MAXIBLOCK CABLE GLANDS 1900/X M

Technical characteristics

IP protection	IP68
UL94 class	V2
Max operating temperature range (surge)	120 °C
Min operating temperature range (surge)	-20 °C
Max operating temperature range	90 °C
Min operating temperature range	-20 °C
Material (Body)	Polyamide PA6.6
Material (Sealing ring)	Neoprene®



MAXIBLOCK CABLE GLANDS 1900/X M

List of products

1900/X M



Type	P	Fixing hole diameter	ØA Min	ØA Max	B	C	L Min	L Max	Colour	Pack qty	Min. pack qty
1900.M12/X	M12X1,5	12.2 mm	3.5 mm	7 mm	15 mm	8 mm	18 mm	22 mm	Grey RAL 7035	100	10
1900.M16/X	M16X1,5	16.2 mm	5 mm	10 mm	19 mm	8 mm	22 mm	27 mm	Grey RAL 7035	100	10
1900.M20/X	M20X1,5	20.5 mm	7 mm	13 mm	25 mm	9 mm	24 mm	30 mm	Grey RAL 7035	50	10
1900.M25/X	M25X1,5	25.4 mm	10 mm	17 mm	30 mm	10 mm	28 mm	39 mm	Grey RAL 7035	30	10
1900.M32/X	M32X1,5	32.5 mm	13 mm	21 mm	36 mm	10 mm	33 mm	44 mm	Grey RAL 7035	20	10
1900.M40/X	M40X1,5	40.5 mm	19 mm	28 mm	46 mm	10 mm	36 mm	45 mm	Grey RAL 7035	10	5
1900.M50/X	M50X1,5	50.5 mm	27 mm	35 mm	55 mm	12 mm	43 mm	52 mm	Grey RAL 7035	10	5
1900.M63/X	M63X1,5	64 mm	34 mm	45 mm	66 mm	12 mm	45 mm	55 mm	Grey RAL 7035	5	5