

MAXIBLOCK CABLE GLANDS 1900/X PG

Standard factory fitted with locknuts with collar, metric Pg thread

Cable glands and accessories for control panels and engineering applications.



MAXIBLOCK CABLE GLANDS 1900/X PG

Technical characteristics

| | |
|---|-----------------|
| IP protection | IP68 |
| UL94 class | V2 |
| Max operating temperature range (surge) | 120 °C |
| Min operating temperature range (surge) | -20 °C |
| Max operating temperature range | 90 °C |
| Min operating temperature range | -20 °C |
| Material (Body) | Polyamide PA6.6 |
| Material (Sealing ring) | Neoprene® |



MAXIBLOCK CABLE GLANDS 1900/X PG

List of products

1900/X Pg



| Type | P | Fixing hole diameter | ØA Min | ØA Max | B | C | L Min | L Max | Colour | Pack qty | Min. pack qty |
|-----------|--------|----------------------|--------|--------|-------|-------|-------|-------|---------------|----------|---------------|
| 1900.07/X | Pg7 | 12.7 mm | 3.5 mm | 7 mm | 15 mm | 8 mm | 18 mm | 22 mm | Grey RAL 7035 | 100 | 10 |
| 1900.09/X | Pg9 | 15.5 mm | 5 mm | 8 mm | 19 mm | 8 mm | 22 mm | 26 mm | Grey RAL 7035 | 100 | 10 |
| 1900.11/X | Pg11 | 18.8 mm | 5 mm | 10 mm | 22 mm | 8 mm | 23 mm | 28 mm | Grey RAL 7035 | 50 | 10 |
| 1900.13/X | Pg13,5 | 20.5 mm | 7 mm | 12 mm | 24 mm | 9 mm | 24 mm | 29 mm | Grey RAL 7035 | 50 | 10 |
| 1900.16/X | Pg16 | 22.6 mm | 10 mm | 14 mm | 27 mm | 10 mm | 26 mm | 31 mm | Grey RAL 7035 | 30 | 10 |
| 1900.21/X | Pg21 | 28.5 mm | 13 mm | 18 mm | 33 mm | 12 mm | 30 mm | 35 mm | Grey RAL 7035 | 20 | 10 |
| 1900.29/X | Pg29 | 37.2 mm | 18 mm | 25 mm | 42 mm | 12 mm | 33 mm | 39 mm | Grey RAL 7035 | 20 | 10 |
| 1900.36/X | Pg36 | 47.2 mm | 20 mm | 32 mm | 53 mm | 14 mm | 42 mm | 49 mm | Grey RAL 7035 | 10 | 5 |
| 1900.42/X | Pg42 | 54.2 mm | 28 mm | 38 mm | 60 mm | 14 mm | 42 mm | 50 mm | Grey RAL 7035 | 5 | 5 |
| 1900.48/X | Pg48 | 60 mm | 37 mm | 45 mm | 66 mm | 15 mm | 45 mm | 55 mm | Grey RAL 7035 | 5 | 5 |