

MAXIBLOCK CABLE GLANDS 1900/X PG

Standard factory fitted with locknuts with collar, metric Pg thread


Cable glands and accessories for control panels and engineering applications.



MAXIBLOCK CABLE GLANDS 1900/X PG

Technical characteristics

IP protection	IP68
UL94 class	V2
Max operating temperature range (surge)	120 °C
Min operating temperature range (surge)	-20 °C
Max operating temperature range	90 °C
Min operating temperature range	-20 °C
Material (Body)	Polyamide PA6.6
Material (Sealing ring)	Neoprene®



MAXIBLOCK CABLE GLANDS 1900/X PG

List of products

1900/X Pg											
											
Type	P	Fixing hole diameter	ØA Min	ØA Max	B	C	L Min	L Max	Colour	Pack qty	Min. pack qty
1900.07/X	Pg7	12.7 mm	3.5 mm	7 mm	15 mm	8 mm	18 mm	22 mm	Grey RAL 7035	100	10
1900.09/X	Pg9	15.5 mm	5 mm	8 mm	19 mm	8 mm	22 mm	26 mm	Grey RAL 7035	100	10
1900.11/X	Pg11	18.8 mm	5 mm	10 mm	22 mm	8 mm	23 mm	28 mm	Grey RAL 7035	50	10
1900.13/X	Pg13,5	20.5 mm	7 mm	12 mm	24 mm	9 mm	24 mm	29 mm	Grey RAL 7035	50	10
1900.16/X	Pg16	22.6 mm	10 mm	14 mm	27 mm	10 mm	26 mm	31 mm	Grey RAL 7035	30	10
1900.21/X	Pg21	28.5 mm	13 mm	18 mm	33 mm	12 mm	30 mm	35 mm	Grey RAL 7035	20	10
1900.29/X	Pg29	37.2 mm	18 mm	25 mm	42 mm	12 mm	33 mm	39 mm	Grey RAL 7035	20	10
1900.36/X	Pg36	47.2 mm	20 mm	32 mm	53 mm	14 mm	42 mm	49 mm	Grey RAL 7035	10	5
1900.42/X	Pg42	54.2 mm	28 mm	38 mm	60 mm	14 mm	42 mm	50 mm	Grey RAL 7035	5	5
1900.48/X	Pg48	60 mm	37 mm	45 mm	66 mm	15 mm	45 mm	55 mm	Grey RAL 7035	5	5