



MAXIBLOCK CABLE GLANDS 1900 GAS

Standard, BSP thread

Cable glands and accessories for control panels and engineering applications.



CERTIFICATES 

 UL 514B  UL 514B

MAXIBLOCK CABLE GLANDS 1900 GAS

Technical characteristics

Material (Body)

Polyamide PA6.6

Material (Sealing ring)

Neoprene®



MAXIBLOCK CABLE GLANDS 1900 GAS

List of products

| 1900 GAS | | | | | | | | | | |
|----------|-------|----------------------|--------|--------|-------|-------|-------|-------|----------------|----------|
| Type | P | Fixing hole diameter | ØA Min | ØA Max | B | L Min | L Max | C | Colour | Pack qty |
| 1900.14 | G1/4" | 13.5 mm | 3 mm | 6.5 mm | 15 mm | 18 mm | 22 mm | 8 mm | Grey RAL 7035 | 100 |
| 1900.38 | G3/8" | 17 mm | 4 mm | 8 mm | 19 mm | 22 mm | 26 mm | 8 mm | Grey RAL 7035 | 100 |
| 1900.12 | G1/2" | 21.5 mm | 7 mm | 12 mm | 24 mm | 24 mm | 29 mm | 10 mm | Grey RAL 7035 | 100 |
| 1900.34 | G3/4" | 27 mm | 13 mm | 18 mm | 33 mm | 30 mm | 35 mm | 12 mm | Grey RAL 7035 | 50 |
| 1900.14N | G1/4" | 13.5 mm | 3 mm | 6.5 mm | 15 mm | 18 mm | 22 mm | 8 mm | Black RAL 9005 | 100 |
| 1900.38N | G3/8" | 17 mm | 4 mm | 8 mm | 19 mm | 22 mm | 26 mm | 8 mm | Black RAL 9005 | 100 |
| 1900.12N | G1/2" | 21.5 mm | 7 mm | 12 mm | 24 mm | 24 mm | 29 mm | 10 mm | Black RAL 9005 | 100 |
| 1900.34N | G3/4" | 27 mm | 13 mm | 18 mm | 33 mm | 30 mm | 35 mm | 12 mm | Black RAL 9005 | 50 |