



MAXIBLOCK CABLE GLANDS 1900 GAS

Standard, BSP thread

Cable glands and accessories for control panels and engineering applications.



CERTIFICATES 

 UL 514B  UL 514B

MAXIBLOCK CABLE GLANDS 1900 GAS

Technical characteristics

IP protection	IP68
UL94 class	V2
Max operating temperature range (surge)	120 °C
Min operating temperature range (surge)	-20 °C
Max operating temperature range	90 °C
Min operating temperature range	-20 °C
Material (Body)	Polyamide PA6.6
Material (Sealing ring)	Neoprene®



MAXIBLOCK CABLE GLANDS 1900 GAS

List of products

1900 GAS										
Type	P	Fixing hole diameter	ØA Min	ØA Max	B	L Min	L Max	C	Colour	Pack qty
1900.14	G1/4"	13.5 mm	3 mm	6.5 mm	15 mm	18 mm	22 mm	8 mm	Grey RAL 7035	100
1900.38	G3/8"	17 mm	4 mm	8 mm	19 mm	22 mm	26 mm	8 mm	Grey RAL 7035	100
1900.12	G1/2"	21.5 mm	7 mm	12 mm	24 mm	24 mm	29 mm	10 mm	Grey RAL 7035	100
1900.34	G3/4"	27 mm	13 mm	18 mm	33 mm	30 mm	35 mm	12 mm	Grey RAL 7035	50
1900.14N	G1/4"	13.5 mm	3 mm	6.5 mm	15 mm	18 mm	22 mm	8 mm	Black RAL 9005	100
1900.38N	G3/8"	17 mm	4 mm	8 mm	19 mm	22 mm	26 mm	8 mm	Black RAL 9005	100
1900.12N	G1/2"	21.5 mm	7 mm	12 mm	24 mm	24 mm	29 mm	10 mm	Black RAL 9005	100
1900.34N	G3/4"	27 mm	13 mm	18 mm	33 mm	30 mm	35 mm	12 mm	Black RAL 9005	50