

MAXIBLOCK CABLE GLANDS 4900 PG

Atex, Pg thread



CERTIFICATES 



IMQ 10 ATEX 028X




2014/34/EU

MAXIBLOCK CABLE GLANDS 4900 PG

Technical characteristics

Material (Body)	Polyamide PA6
Material (Sealing ring)	Neoprene®
UL94 class	V2
Max application temperature	75 °C
Min application temperature	-20 °C
IP protection	65



MAXIBLOCK CABLE GLANDS 4900 PG

List of products

4900 Pg										
Type	Thread	Fixing hole diameter	Minimum diameter of clamping	Maximum diameter of clamping	Opening key (for the head)	Thread height	Minimum width of clamping	Maximum width of clamping	Colour	Pack qty
4900.07	Pg7	12.7 mm	3.5 mm	6.5 mm	15 mm	8 mm	18 mm	22 mm	Grey RAL 7035	100
4900.09	Pg9	15.5 mm	6.5 mm	8 mm	19 mm	8 mm	22 mm	26 mm	Grey RAL 7035	100
4900.11	Pg11	18.8 mm	8 mm	10 mm	22 mm	8 mm	23 mm	28 mm	Grey RAL 7035	100
4900.13	Pg13,5	20.5 mm	9 mm	12 mm	24 mm	9 mm	24 mm	29 mm	Grey RAL 7035	100
4900.16	Pg16	22.6 mm	10 mm	14 mm	27 mm	10 mm	26 mm	31 mm	Grey RAL 7035	50
4900.21	Pg21	28.5 mm	14 mm	18 mm	33 mm	12 mm	30 mm	35 mm	Grey RAL 7035	50
4900.29	Pg29	37.2 mm	18 mm	22 mm	42 mm	12 mm	33 mm	39 mm	Grey RAL 7035	25
4900.36	Pg36	47.2 mm	22 mm	32 mm	53 mm	14 mm	42 mm	49 mm	Grey RAL 7035	10
4900.42	Pg42	54.2 mm	28 mm	38 mm	60 mm	14 mm	42 mm	50 mm	Grey RAL 7035	5
4900.48	Pg48	60 mm	38 mm	48 mm	66 mm	15 mm	45 mm	55 mm	Grey RAL 7035	5

