

# MAXIBLOCK CABLE GLANDS 4901 PG

*Atex, Pg thread, extended thread*



CERTIFICATES 



IMQ 10 ATEX 028X




2014/34/EU

# MAXIBLOCK CABLE GLANDS 4901 PG

## *Technical characteristics*

|                             |               |
|-----------------------------|---------------|
| Material (Body)             | Polyamide PA6 |
| Material (Sealing ring)     | Neoprene®     |
| UL94 class                  | V2            |
| Max application temperature | 75 °C         |
| Min application temperature | -20 °C        |
| IP protection               | 65            |



# MAXIBLOCK CABLE GLANDS 4901 PG

## List of products

### 4901 Pg



| Type    | Thread | Fixing hole diameter | Minimum diameter of clamping | Maximum diameter of clamping | Opening key (for the head) | Thread height | Minimum width of clamping | Maximum width of clamping | Colour        | Pack qty |
|---------|--------|----------------------|------------------------------|------------------------------|----------------------------|---------------|---------------------------|---------------------------|---------------|----------|
| 4901.07 | Pg7    | 12.7 mm              | 3.5 mm                       | 6.5 mm                       | 15 mm                      | 15 mm         | 18 mm                     | 22 mm                     | Grey RAL 7035 | 100      |
| 4901.09 | Pg9    | 15.5 mm              | 6.5 mm                       | 8 mm                         | 19 mm                      | 15 mm         | 22 mm                     | 26 mm                     | Grey RAL 7035 | 100      |
| 4901.11 | Pg11   | 18.8 mm              | 8 mm                         | 10 mm                        | 22 mm                      | 15 mm         | 23 mm                     | 28 mm                     | Grey RAL 7035 | 100      |
| 4901.13 | Pg13,5 | 20.5 mm              | 9 mm                         | 12 mm                        | 24 mm                      | 15 mm         | 24 mm                     | 29 mm                     | Grey RAL 7035 | 100      |
| 4901.16 | Pg16   | 22.6 mm              | 10 mm                        | 14 mm                        | 27 mm                      | 15 mm         | 26 mm                     | 31 mm                     | Grey RAL 7035 | 50       |
| 4901.21 | Pg21   | 28.5 mm              | 14 mm                        | 18 mm                        | 33 mm                      | 15 mm         | 30 mm                     | 35 mm                     | Grey RAL 7035 | 50       |
| 4901.29 | Pg29   | 37.2 mm              | 18 mm                        | 22 mm                        | 42 mm                      | 15 mm         | 33 mm                     | 39 mm                     | Grey RAL 7035 | 25       |
| 4901.36 | Pg36   | 47.2 mm              | 22 mm                        | 32 mm                        | 53 mm                      | 18 mm         | 42 mm                     | 49 mm                     | Grey RAL 7035 | 10       |
| 4901.42 | Pg42   | 54.2 mm              | 28 mm                        | 38 mm                        | 60 mm                      | 18 mm         | 42 mm                     | 50 mm                     | Grey RAL 7035 | 5        |
| 4901.48 | Pg48   | 60 mm                | 38 mm                        | 45 mm                        | 66 mm                      | 18 mm         | 45 mm                     | 55 mm                     | Grey RAL 7035 | 5        |