

# MAXIBLOCK CABLE GLANDS 4901 PG

*Atex, Pg thread, extended thread*



CERTIFICATES 



IMQ 10 ATEX 028X




2014/34/EU

# MAXIBLOCK CABLE GLANDS 4901 PG

## *Technical characteristics*

Material (Body)	Polyamide PA6
Material (Sealing ring)	Neoprene®
UL94 class	V2
Max application temperature	75 °C
Min application temperature	-20 °C
IP protection	65



# MAXIBLOCK CABLE GLANDS 4901 PG

## List of products

### 4901 Pg



Type	Thread	Fixing hole diameter	Minimum diameter of clamping	Maximum diameter of clamping	Opening key (for the head)	Thread height	Minimum width of clamping	Maximum width of clamping	Colour	Pack qty
4901.07	Pg7	12.7 mm	3.5 mm	6.5 mm	15 mm	15 mm	18 mm	22 mm	Grey RAL 7035	100
4901.09	Pg9	15.5 mm	6.5 mm	8 mm	19 mm	15 mm	22 mm	26 mm	Grey RAL 7035	100
4901.11	Pg11	18.8 mm	8 mm	10 mm	22 mm	15 mm	23 mm	28 mm	Grey RAL 7035	100
4901.13	Pg13,5	20.5 mm	9 mm	12 mm	24 mm	15 mm	24 mm	29 mm	Grey RAL 7035	100
4901.16	Pg16	22.6 mm	10 mm	14 mm	27 mm	15 mm	26 mm	31 mm	Grey RAL 7035	50
4901.21	Pg21	28.5 mm	14 mm	18 mm	33 mm	15 mm	30 mm	35 mm	Grey RAL 7035	50
4901.29	Pg29	37.2 mm	18 mm	22 mm	42 mm	15 mm	33 mm	39 mm	Grey RAL 7035	25
4901.36	Pg36	47.2 mm	22 mm	32 mm	53 mm	18 mm	42 mm	49 mm	Grey RAL 7035	10
4901.42	Pg42	54.2 mm	28 mm	38 mm	60 mm	18 mm	42 mm	50 mm	Grey RAL 7035	5
4901.48	Pg48	60 mm	38 mm	45 mm	66 mm	18 mm	45 mm	55 mm	Grey RAL 7035	5