

MAXIBRASS CABLE GLANDS 2900 M

Standard, metric thread M 1,5 pitch



CERTIFICATES 



UL 514B



UL 514B



EN 62444:2013



EN 62444: 2013

MAXIBRASS CABLE GLANDS 2900 M

Technical characteristics


Material (Body)	Nickel plated brass
Material (Sealing ring)	Neoprene®
Material (Cable grip insert)	Polyamide PA6.6
Material (O-Ring)	Nitrile 70 sh A
Max operating temperature range	100 °C
Min operating temperature range	-25 °C



MAXIBRASS CABLE GLANDS 2900 M

List of products

2900 M



Type	P	Fixing hole diameter	ØA Min	ØA Max	B	E	C	L Min	L Max	Pack qty
2900.M12N	M12X1,5	12.2 mm	3 mm	7 mm	16 mm	18 mm	6.5 mm	16 mm	20 mm	100
2900.M16N	M16X1,5	16.2 mm	4.5 mm	10 mm	20 mm	23 mm	7 mm	20 mm	25 mm	100
2900.M20N	M20X1,5	20.5 mm	7 mm	13 mm	24 mm	27 mm	8 mm	20 mm	27 mm	50
2900.M25N	M25X1,5	25.4 mm	10 mm	17 mm	29 mm	32 mm	8 mm	24 mm	30 mm	50
2900.M32N	M32X1,5	32.5 mm	11 mm	21 mm	36 mm	40 mm	9 mm	27 mm	34 mm	25
2900.M40N	M40X1,5	40.5 mm	19 mm	28 mm	45 mm	50 mm	9 mm	34 mm	42 mm	10
2900.M50N	M50X1,5	50.5 mm	26 mm	35 mm	54 mm	60 mm	10 mm	35 mm	43 mm	8
2900.M63N	M63X1,5	64 mm	34 mm	45 mm	67 mm	74 mm	15 mm	40 mm	52 mm	5