




MAXIBRASS CABLE GLANDS 2901 M

Extended thread, metric thread M 1,5 pitch




CERTIFICATES 

 UL 514B  UL 514B  EN 62444: 2013

MAXIBRASS CABLE GLANDS 2901 M

Technical characteristics

Material (Body)	Nickel plated brass
Material (Sealing ring)	Neoprene®
Material (Cable grip insert)	Polyamide PA6.6
Material (O-Ring)	Nitrile 70 sh A
Max operating temperature range	100 °C
Min operating temperature range	-25 °C



MAXIBRASS CABLE GLANDS 2901 M

List of products

2901 M



Type	P	Fixing hole diameter	ØA Min	ØA Max	B	E	C	L Min	L Max	Pack qty
2901.M12N	M12X1,5	12.2 mm	3 mm	7 mm	16 mm	18 mm	12 mm	16 mm	20 mm	100
2901.M16N	M16X1,5	16.2 mm	4.5 mm	10 mm	20 mm	23 mm	12 mm	20 mm	25 mm	100
2901.M20N	M20X1,5	20.5 mm	7 mm	13 mm	24 mm	27 mm	12 mm	20 mm	27 mm	50
2901.M25N	M25X1,5	25.4 mm	10 mm	17 mm	29 mm	32 mm	12 mm	24 mm	30 mm	50
2901.M32N	M32X1,5	32.5 mm	11 mm	21 mm	36 mm	40 mm	15 mm	27 mm	34 mm	25
2901.M40N	M40X1,5	40.5 mm	19 mm	28 mm	45 mm	50 mm	15 mm	34 mm	42 mm	10
2901.M50N	M50X1,5	50.5 mm	26 mm	35 mm	54 mm	60 mm	15 mm	35 mm	43 mm	8