




## MAXIBRASS CABLE GLANDS 2901 M

*Extended thread, metric thread M 1,5 pitch*



CERTIFICATES 

 UL 514B  UL 514B  EN 62444: 2013

# MAXIBRASS CABLE GLANDS 2901 M

## *Technical characteristics*


|                                 |                     |
|---------------------------------|---------------------|
| Material (Body)                 | Nickel plated brass |
| Material (Sealing ring)         | Neoprene®           |
| Material (Cable grip insert)    | Polyamide PA6.6     |
| Material (O-Ring)               | Nitrile 70 sh A     |
| Max operating temperature range | 100 °C              |
| Min operating temperature range | -25 °C              |



# MAXIBRASS CABLE GLANDS 2901 M

## List of products

### 2901 M



| Type      | P       | Fixing hole diameter | ØA Min | ØA Max | B     | E     | C     | L Min | L Max | Pack qty |
|-----------|---------|----------------------|--------|--------|-------|-------|-------|-------|-------|----------|
| 2901.M12N | M12X1,5 | 12.2 mm              | 3 mm   | 7 mm   | 16 mm | 18 mm | 12 mm | 16 mm | 20 mm | 100      |
| 2901.M16N | M16X1,5 | 16.2 mm              | 4.5 mm | 10 mm  | 20 mm | 23 mm | 12 mm | 20 mm | 25 mm | 100      |
| 2901.M20N | M20X1,5 | 20.5 mm              | 7 mm   | 13 mm  | 24 mm | 27 mm | 12 mm | 20 mm | 27 mm | 50       |
| 2901.M25N | M25X1,5 | 25.4 mm              | 10 mm  | 17 mm  | 29 mm | 32 mm | 12 mm | 24 mm | 30 mm | 50       |
| 2901.M32N | M32X1,5 | 32.5 mm              | 11 mm  | 21 mm  | 36 mm | 40 mm | 15 mm | 27 mm | 34 mm | 25       |
| 2901.M40N | M40X1,5 | 40.5 mm              | 19 mm  | 28 mm  | 45 mm | 50 mm | 15 mm | 34 mm | 42 mm | 10       |
| 2901.M50N | M50X1,5 | 50.5 mm              | 26 mm  | 35 mm  | 54 mm | 60 mm | 15 mm | 35 mm | 43 mm | 8        |