

MAXIBRASS CABLE GLANDS 2911 M

Extended thread and reduced cable entry, metric thread M 1,5 pitch



CERTIFICATES 



UL 514B



UL 514B



EN 62444:2013



EN 62444: 2013

MAXIBRASS CABLE GLANDS 2911 M

Technical characteristics


Material (Body)	Nickel plated brass
Material (Sealing ring)	Neoprene®
Material (Cable grip insert)	Polyamide PA6.6
Material (O-Ring)	Nitrile 70 sh A
Max operating temperature range	100 °C
Min operating temperature range	-25 °C



MAXIBRASS CABLE GLANDS 2911 M

List of products

2911 M



Type	P	Fixing hole diameter	ØA Min	ØA Max	B	E	C	L Min	L Max	Pack qty
2911.M12N	M12X1,5	12.2 mm	1 mm	5 mm	16 mm	18 mm	12 mm	16 mm	20 mm	100
2911.M16N	M16X1,5	16.2 mm	2.5 mm	7 mm	20 mm	23 mm	12 mm	20 mm	25 mm	100
2911.M20N	M20X1,5	20.5 mm	5 mm	10 mm	24 mm	27 mm	12 mm	20 mm	27 mm	50
2911.M25N	M25X1,5	25.4 mm	6 mm	13 mm	29 mm	32 mm	12 mm	24 mm	30 mm	50
2911.M32N	M32X1,5	32.5 mm	7 mm	14 mm	36 mm	40 mm	15 mm	27 mm	34 mm	25
2911.M40N	M40X1,5	40.5 mm	13 mm	23 mm	45 mm	50 mm	15 mm	34 mm	42 mm	10
2911.M50N	M50X1,5	50.5 mm	20 mm	29 mm	54 mm	60 mm	15 mm	35 mm	43 mm	8