



MAXIBRASS CABLE GLANDS 2900 PG

Standard, Pg thread



CERTIFICATES 

 UL 514B  UL 514B

MAXIBRASS CABLE GLANDS 2900 PG

Technical characteristics

Material (Body)	Nickel plated brass
Material (Sealing ring)	Neoprene®
Material (Cable grip insert)	Polyamide PA6.6
Material (O-Ring)	Nitrile 70 sh A
Max operating temperature range	100 °C
Min operating temperature range	-25 °C



MAXIBRASS CABLE GLANDS 2900 PG

List of products

2900 Pg



Type	P	Fixing hole diameter	ØA Min	ØA Max	B	E	C	L Min	L Max	Pack qty
2900.07N	Pg7	12.7 mm	3 mm	7 mm	16 mm	18 mm	5 mm	16 mm	20 mm	100
2900.09N	Pg9	15.5 mm	4 mm	8 mm	17 mm	19 mm	6 mm	17 mm	23 mm	100
2900.11N	Pg11	18.8 mm	4.5 mm	10 mm	20 mm	23 mm	6 mm	20 mm	25 mm	100
2900.13N	Pg13,5	20.5 mm	5 mm	12 mm	22 mm	25 mm	6.5 mm	20 mm	26 mm	50
2900.16N	Pg16	22.6 mm	7 mm	13 mm	24 mm	27 mm	6.5 mm	20 mm	27 mm	50
2900.21N	Pg21	28.5 mm	10 mm	17 mm	30 mm	33 mm	7 mm	24 mm	30 mm	50
2900.29N	Pg29	37.2 mm	17 mm	25 mm	40 mm	45 mm	8 mm	30 mm	37 mm	25
2900.36N	Pg36	47.2 mm	20 mm	32 mm	50 mm	55 mm	8 mm	38 mm	48 mm	10
2900.42N	Pg42	54.2 mm	28 mm	38 mm	57 mm	63 mm	10 mm	39 mm	48 mm	5
2900.48N	Pg48	60 mm	34 mm	45 mm	67 mm	74 mm	15 mm	40 mm	52 mm	5