



MAXIBRASS CABLE GLANDS 2910 PG

Reduced cable entry, Pg thread



CERTIFICATES 

 UL 514B  UL 514B

MAXIBRASS CABLE GLANDS 2910 PG

Technical characteristics

Material (Body)	Nickel plated brass
Material (Sealing ring)	Neoprene®
Material (Cable grip insert)	Polyamide PA6.6
Material (O-Ring)	Nitrile 70 sh A
Max operating temperature range	100 °C
Min operating temperature range	-25 °C



MAXIBRASS CABLE GLANDS 2910 PG

List of products

2910 Pg



Type	P	Fixing hole diameter	ØA Min	ØA Max	B	E	C	L Min	L Max	Pack qty
2910.07N	Pg7	12.7 mm	1 mm	5 mm	16 mm	18 mm	5 mm	16 mm	20 mm	100
2910.09N	Pg9	15.5 mm	2 mm	6 mm	17 mm	19 mm	6 mm	17 mm	23 mm	100
2910.11N	Pg11	18.8 mm	2.5 mm	7 mm	20 mm	23 mm	6 mm	20 mm	25 mm	100
2910.13N	Pg13,5	20.5 mm	4 mm	10 mm	22 mm	25 mm	6.5 mm	20 mm	26 mm	50
2910.16N	Pg16	22.6 mm	5 mm	10 mm	24 mm	27 mm	6.5 mm	20 mm	27 mm	50
2910.21N	Pg21	28.5 mm	6 mm	13 mm	30 mm	33 mm	7 mm	24 mm	30 mm	50
2910.29N	Pg29	37.2 mm	11 mm	20 mm	40 mm	45 mm	8 mm	30 mm	37 mm	25
2910.36N	Pg36	47.2 mm	18 mm	26 mm	50 mm	55 mm	8 mm	38 mm	48 mm	10
2910.42N	Pg42	54.2 mm	24 mm	31 mm	57 mm	63 mm	10 mm	39 mm	48 mm	5
2910.48N	Pg48	60 mm	27 mm	39 mm	67 mm	74 mm	15 mm	40 mm	52 mm	5